

EPPO-ICB-B-230V-2W3P-20A

Explosion Proof Power Plug and Receptacle - Class I, II, III - 20A, 230V - Circuit Breaker Switch

Product ID: 266395

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPPO-ICB-B-230V-2W3P-20A Explosion Proof Receptacle and Plug

Receptacle Specs:

Listing: NRTL Listed for United States, Canada

Dimensions: 10 1/2" x 9 3/4" x 5 3/4"

Weight: -

Voltage Rating: 230V

Current Rating: 20 Amps

HP: 5HP @ 240V 1PH

Configuration: 2-Wire, 3-Pole

Protection: On/Off Circuit Breaker

Aux Contact: Late-make Early-break, Rated @ 10A, 1/3 HP 125/250V AC

Materials: Copper Free Aluminum

Finish: Electrostatically Applied Polyester/Epoxy

Mount: Wall

Wiring: Regular Stranding #10 Maximum

Hub Configuration: Feed Thru or Dead End

Hub Size: 1" NPT

Plug Specs:

Listing: NRTL Listed for United States, Canada

Dimensions: 6 11/16" x 3"

Ratings

Class I, Divisions 1 & 2 Group B, C, D

Class 1, Zones 1 & 2 IIB+H2, IIA

Class II, Divisions 1 & 2 Group F, G

Class III

NEMA 3, 4, 4X 7(B,C,D), 9(F,G)

Weight: -

Voltage Rating: 230V

Current Rating: 20 Amps

HP: 5HP @ 240V 1PH

Configuration: 2-Wire, 3-Pole

Materials: Copper Free Aluminum

Finish: Electrostatically Applied Polyester/Epoxy

Mount: -

Wiring: Regular Stranding #10 Maximum

Hub Configuration: -

Hub Size: 1" NPT

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EPPO-ICB-B-230V-2W3P-20A Explosion Proof Receptacle and Plug is approved for Class I, Division 1 & 2, Class II, Division 1 & 2 and Class III sites and provides a safe and secure power connection for portable or stationary electrical devices and equipment in hazardous locations. This 2-wire, 3-pole unit is constructed of copper-free aluminum and operates with 230V AC. Rated at 20 amps, both devices can be used in Class I, Group B rated locations.

The explosion proof power receptacle and plug is designed for use in combustible work sites, including Class I, Group B. This 20-amp receptacle features compatibility with 230V AC. This 2-wire, 3-pole unit is constructed of copper-free aluminum with an electrostatically applied polyester/epoxy finish and contains an integral circuit breaker which provides short circuit and thermal overload protection as well as manually operable protection during connection and disconnection of electrical cables. This unit is easily wall mounted via two screw slot tabs at the side of the housing and contains a feed-thru or dead-end configuration with 1" NPT hub size.

The explosion proof plug takes on an octagon-style design. Insulators have high mechanical and dielectric strength and are low arc tracking. The device takes on a NEMA 4X rating when used with a compatible receptacle and a tightened locking ring. This plug is suitable for Type P marine cable.

Integral circuit protection: This unit contains a circuit breaker to allow safe, 20 Amp at 230V AC max operation. The circuit breaker also gives protection against short circuits and provides added thermal time delay overload protection. The plug and receptacle contacts cannot be made or broken under load. When the plug is inserted, the plug and receptacle contacts engage before the switch closes. When the plug is withdrawn, the switch opens before the plug and receptacle contacts disengage. This provides the maximum safety of a dead front receptacle. Arcing is isolated in a flame and dust-tight chamber. No special interlock device or manual switch, operators simply pull the plug straight out.

Interchangeability: The receptacle and plug are fully interchangeable with configured and certified to UL1686 devices, such as Crouse-Hinds® Arktite® or Appleton® Powertite®. Standard location receptacle bolt hole patterns match competitive back boxes so users can perform upgrades without changing back boxes in instances where changing the conduit system is difficult.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Lighting, Wet areas or Locations Where Combustible Dust is Present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)





EPPO-ICB-B-230V-2W3P-20A

Product ID: 266395

Export Control Classification Number (ECCN): EAR99

Options:

EPPO-ICB-B-230V-2W3P-20A-**Termination**

Example: EPPO-ICB-B-230V-2W3P-20A-**FT**

Termination	
FEED-THRU	-FT
DEAD END	-DE

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)