


IND-HVAC-DTW-UVC-R4-SS-48-3L-220V

48" High Output UV Air Duct Disinfection 3-Lamp Fixture - UV-C - Destroys Airborne Bacteria & Viruses - 220V - 79.8W Total UV Output

Product ID: 268928

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

IND-HVAC-DTW-UVC-R4-SS-48-3L-220V High Output Air Duct Disinfection System

Lamp Technology: UV-C Fluorescent

Exterior Housing Dimensions: 16-13/16"H x 8-1/8"W x 4-7/16"D

Depth (Inside Duct) for Partial Internal Mount: 51"

Weight: -

Voltage: 220V AC, 50/60 Hz

Wattage: 120W Per Lamp

Total Watts: 360W

UV Output: 26.6W per lamp

Total UV Output: 79.8W

Irradiance (single lamp): 240 uW/cm2 @ 1 meter

Expected Lifespan: 8,000+ Hours

UV Wavelength: 254nm peak

Lamp Base: G13 (Medium Bi-Pin)

Replacement Lamp: FRL-48-1X-T8-40W-UV-C

Beam Angle: 360°

Light Configuration: Flood

Amps: 1.25A @ 220V

Ambient Operating Temp Range: -

Materials: 304 Stainless Steel Enclosure

Indicator Lights: Operational Light (confirms on) and Replace Lamp (lamp no longer functional) indicator lamps

Ratings/Features

NRTL Listed to UL 508A

NRTL Listed to CSA C22.2 No. 14

T8 Bulb Shape

Short-wave Germicidal Light

Destroys Airborne Bacteria and Viruses

Non-Ozone Producing Germicidal UV Lamp

EPA Reg. No 98409-1

EPA Est. No. 98409-TX-1

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

Mounting: Partial Internal Duct Mount

E-mail: sales@larsonelectronics.com

PLEASE NOTE: UV-C light can cause temporary or permanent loss of vision, and temporary acute redness or ulceration (mild to severe sunburn) to exposed skin. To prevent exposure, do not operate the device in any application that allows UV-C light to be visible during operation. NEVER LOOK DIRECTLY AT THE BULB OR DISINFECTING TARGET ZONE. DO NOT touch bulb with bare hands. The oils in your skin will damage the lamp. Fingerprints will result in reduced performance and significantly reduce the lifespan of the lamp unless they are removed with alcohol. Please read instruction manual for UV safety requirements before operating.

This unit is Made In USA - Manufactured in Texas

The IND-HVAC-DTW-UVC-R4-SS-48-3L-220V from Larson Electronics is a High Output Air Duct Disinfection System that works to disinfect air moving through a duct system via germicidal ultraviolet (UV) rays. This unit helps to control the spread of airborne cold and flu virus as well as other airborne transmitted disease. This anodized aluminum air duct disinfection system features three of 220 watt UV bulbs that each produce 26.6 watts (79.8W total) of UV output at a wavelength of 254nm. The IND-HVAC-DTW-UVC-R4-SS-48-3L-220V is designed to be mounted inside a high output air duct and operates on 220V AC current.

Please note: This product produces UV light. Make sure to follow all safety guidelines and protocols found in the user manual.

The IND-HVAC-DTW-UVC-R4-SS-48-3L-220V is a powerful sanitation solution for industrial sites and commercial facilities. Equipped with three UVC high output fluorescent lamps, this system offers 79.8 total watts of UV output at a wavelength of 254nm. The lights have an expected lifespan of 8,000+ hours and emit a flood beam pattern. The IND-HVAC-DTW-UVC-R4-SS-48-3L-220V can be used continuously in air ducts such as those found in HVAC systems.

Operation: This high output air duct disinfection system projects ultraviolet rays inside the air duct it is mounted in. The air flowing through the duct that passes through the UV rays is then sanitized. Bacteria and viruses present in the air that passes through the UV rays produced by the fixture are destroyed. The air moving through the duct is constantly being purified as it flows through the UV rays being produced by the fixture.

Construction: The enclosure of the IND-HVAC-DTW-UVC-R4-SS-48-3L-220V is built from 304 stainless steel. In-Operation and Replace-Lamp indicator lamps allows for operators to check the status of the UV bulb(s) without removing the fixture from the air duct or being exposed to harmful UV radiation.

Mounting: The IND-HVAC-DTW-UVC-R4-SS-48-3L-220V is designed to be mounted inside an air duct. The system is intended to be mounted in a partial internal style with the bulb(s) being mounted inside of the air duct and the electronics mounted on the outside of the duct.

Note on Environment: Sunlight and visible light fixtures do not impact the effectiveness of the disinfecting on this UVC sanitation product. Metal halide, high pressure sodium, fluorescent, and LED light fixtures can be left on. The UV radiation emitted from this product is not disrupted by any type of lighting in the environment. Put simply, NO it DOES NOT need to be dark in the area you plan to disinfect. The UV radiation is harmful to the eyes and skin, and that is why you should not be in the area while it is in operation. Please see user manual for additional safety information.

Applications: This ultraviolet UV air duct disinfection system can be used to continuously disinfect air of mold, allergens, airborne bacteria, viruses, and germs. The IND-HVAC-DTW-UVC-R4-SS-48-3L-220V is ideal for use in restaurants, hospitals, clinics, laboratories, nursing homes, schools, food processing facilities, office buildings, conference rooms, universities, clean rooms, and many more. Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Frequently Asked Questions (FAQ)

IND-HVAC-DTW-UVC-R4-SS-48-3L-220V

Product ID: 268928

Warranty: 6 Months

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [Catalog Page - Product Series](#)
- [Certificate 1, Misc](#)
- [Certificate 4, Misc](#)
- [Dimensional Drawing 2D](#)
- [Eye Safety Information/Certificate](#)
- [Lighting Facts & Information](#)
- [MSDS \(Material Safety Data Sheet](#)
- [Operations Manual](#)
- [Spectrum Curve \(Wavelength Graph\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [Video1](#)
- [Video2](#)
- [Video3](#)
- [Video4](#)
- [Video5](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)