

1583B Paired - Category 5e Unbonded-Pair Cable

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : No. 8 for DataTwist Cables (Modified Western Electric).pdf</p>
--	--

Description:

24 AWG solid bare copper conductors, non-plenum, Polyolefin insulation, twisted pairs, rip cord, see color code chart (below), Fluorescent Pink PVC jacket.

SUITABLE APPLICATIONS:

Suitable Applications	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422
-----------------------	--

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PO - Polyolefin
---------------------	-----------------

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material Trade Name	DataBrite®
Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

1583B Paired - Category 5e Unbonded-Pair Cable

Overall Nominal Diameter	.195 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +80°C
Bulk Cable Weight	29 lbs/1000 ft.
Max. Recommended Pulling Tension	35 lbs.
Min. Bend Radius (Install)	0.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR, UL444
CEC/C(UL) Specification	CMR
IEC Specification	11801 Category 5
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
TIA/EIA Specification	568-B.2 Category 5e
Other Specification	NEMA WC-63.1 Category 5e, UL Verified to Category 5e

FLAME TEST:

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	1585A
Non-Plenum Number	1583A

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	330 pF/100 m
Nominal Velocity of Propagation	70 %
Maximum Delay (ns/100 m)	538 @ 100MHz ns/100 m
Maximum Delay Skew (ns/100m)	45 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9.38 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	3 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :

1583B Paired - Category 5e Unbonded-Pair Cable

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	65.3	62.3	63.0	60.3	20.0	23
4	4.1	56.3	53.3	51.0	49.2	23.0	23.0
8	5.8	51.8	48.8	46.0	43.0	24.5	24.5
10	6.5	50.3	47.3	43.0	40.8	25.0	25.0
16	8.2	47.3	44.3	39.0	36.0	25.0	25.0
20	9.3	45.8	42.8	36.5	33.5	25.0	25.0
25	10.4	44.3	41.3	33.9	30.9	24.3	24.3
31.25	11.7	42.9	39.9	31.0	28.2	23.6	23.6
62.5	17.0	38.4	35.4	22.0	19.0	21.5	21.5
100	22.0	35.3	32.3	14.0	10.3	20.1	20.1
155	28.1	32.5	29.5	4.4	1.4	15.8	
200	32.0	30.8	27.8	4.0	1.0	15.0	

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.8	60.8
4	100 ± 15	100 ± 15	51.7	48.7
8	100 ± 15	100 ± 15	45.7	42.7
10	100 ± 15	100 ± 15	43.8	40.8
16	100 ± 15	100 ± 15	39.7	36.7
20	100 ± 15	100 ± 15	37.7	34.7
25	100 ± 15	100 ± 15	35.8	32.8
31.25	100 ± 15	100 ± 15	33.9	30.9
62.5	100 ± 15	100 ± 15	27.8	24.9
100	100 ± 15	100 ± 15	23.8	20.8
155	100 ± 25	100 ± 15	19.9	16.9
200	100 ± 25	100 ± 15	17.7	14.7

NOTES:

Notes

Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1583B T301000	4 PR #24 PP PVC	1000	20	MAGENTA, CORONA	C
1583B T30U1000	4 PR #24 PP PVC	U1000	19	MAGENTA, CORONA	

C = CRATE REEL PUT-UP.

Revision Number: 1

Revision Date: 04-12-2006

1583B Paired - Category 5e Unbonded-Pair Cable

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.