

8255 Coax - 93 Ohm

For more Information  
please call

1-800-Belden1

**Description:**

93 ohm, RG-62B/U type, 24 AWG stranded (7x32) .024" bare copper-covered steel conductor, semi-solid polyethylene insulation, BC braid shield (95% coverage), non-contaminating PVC jacket.

**Physical Characteristics (Overall)****Conductor****AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	24	7x32	BCCS - Bare Copper Covered Steel	.024

**Insulation****Insulation Material:**

Insulation Material	Dia. (in.)
Semi-Solid PE - Semi-Solid Polyethylene	.146

**Outer Shield****Outer Shield Material:**

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material
PVCNC - Polyvinyl Chloride Non-Contaminating

**Overall Cable**

**Overall Nominal Diameter:** 0.242 in.

**Mechanical Characteristics (Overall)**

<b>Operating Temperature Range:</b>	-40°C To +80°C
<b>UL Temperature Rating:</b>	60°C (UL AWM Style 1354)
<b>Bulk Cable Weight:</b>	32 lbs/1000 ft.
<b>Max. Recommended Pulling Tension:</b>	75 lbs.
<b>Min. Bend Radius (Install)/Minor Axis:</b>	2.500 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

<b>NEC/(UL) Specification:</b>	CMX
<b>CEC/C(UL) Specification:</b>	CMX
<b>AWM Specification:</b>	UL Style 1354 (30 V 60°C)
<b>EU CE Mark:</b>	Yes
<b>EU Directive 2000/53/EC (ELV):</b>	Yes
<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	10/01/2005
<b>EU Directive 2002/96/EC (WEEE):</b>	Yes

EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
RG Type:	62B/U

**Flame Test**

UL Flame Test:	UL1685 UL Loading, VW-1
----------------	-------------------------

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Electrical Characteristics (Overall)****Nom. Characteristic Impedance:**

Impedance (Ohm)

93

**Nom. Inductance:**

Inductance (μH/ft)

0.116

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/ft)

13.5

**Nominal Velocity of Propagation:**

VP (%)

84

**Nominal Delay:**

Delay (ns/ft)

1.21

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

59.0

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

2.9

**Nom. Attenuation:**

Freq. (MHz) Attenuation (dB/100 ft.)

1	0.3
10	0.9
50	2.0
100	2.9
200	4.2
400	6.1
700	8.6
900	10.1
1000	11.1

**Max. Operating Voltage - UL:**

Voltage

30 V RMS (UL AWM Style 1354)

**Max. Operating Voltage - Non-UL:**

Voltage

750 V RMS

**Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8255 0101000	1,000 FT	36.000 LB	BLACK	C	RG-62B/U TYPE 93OHM COAX
8255 010500	500 FT	16.500 LB	BLACK		RG-62B/U TYPE 93OHM COAX

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 05-14-2007

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.