

For more Information
 please call

1-800-Belden1

**Description:**

100 Ohm twinaxial cable, 20AWG stranded (7x28) one tinned, one bare copper conductor, FEP insulation, overall FEP dielectric, Duofoil® + tinned copper braid shield 85%, FEP jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	7x28	TC - Tinned Copper	.037
			BC - Bare Copper	

Insulation**Insulation Material:**

Insulation Trade Name	Insulation Material	Wall Thickness (in.)
Teflon®	FEP - Fluorinated Ethylene Propylene	.074

Inner Jacket**Inner Jacket Material:**

Inner Jacket Trade Name	Inner Jacket Material	Nom. Dia. (in.)
Teflon®	FEP - Fluorinated Ethylene Propylene	.201

Outer Shield**Outer Shield Material:**

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	85

Outer Jacket**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material
Teflon®	FEP - Fluorinated Ethylene Propylene

Overall Cable

Overall Nominal Diameter: 0.259 in.

Pair**Pair Color Code Chart:**

Number	Color
1	Natural & Natural

Mechanical Characteristics (Overall)

Operating Temperature Range: -70°C To +200°C

Bulk Cable Weight: 52 lbs/1000 ft.

Max. Recommended Pulling Tension: 88 lbs.

Min. Bend Radius (Install)/Minor Axis: 5.400 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

Flame Test

UL Flame Test: NFPA 262

C(UL) Flame Test: FT6

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	9207

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
100

Nom. Inductance:

Inductance (μH/ft)
0.155

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
14.0

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
23.0

Nominal Velocity of Propagation:

VP (%)
69.5

Nominal Delay:

Delay (ns/ft)
1.41

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
9.5

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
2.5

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.3
10	1.2
50	2.8
100	4.1
200	6.4
300	8.4
400	10.2

Max. Operating Voltage - UL:

Voltage
300 V RMS

Notes (Overall)

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
89207 010100	100 FT	6.700 LB	BLACK	C	2#20 FEP FEP SH FEP
89207 0101000	1,000 FT	55.000 LB	BLACK	C	2#20 FEP FEP SH FEP
89207 010500	500 FT	27.500 LB	BLACK	C	2#20 FEP FEP SH FEP

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.