HUBBELL PREMISE WIRING WORK STATION



Seamless Hubbell System Integration.

Universal Keystone Design fits in all Hubbell Products.

Transmit Audio/Video Signal.

110 Style Termination (UTP).



High-impact, flame-

retardant polymer.

Audio Video Connectors, RCA, 110

Standard 110-style termination.

Deliver Composite or Component AV Signals.

Recessed or flush connection designed for poke-though applications.

SPECIFICATIONS

Connector:

Body: Brass
Shell: Plastic
Plating: Nickel 100µ"

Contact: Nickel over Phosphorous Bronze

Performance:

Distance:

Composite: Maximum 100 ft.
Component: Maximum 75 ft.

Mating Cycles: 500+

AV Connector Body Material: flame retardant polymer rated UL 94V-0.

 Insulator Color: Blue, Green, Red, White, and Yellow. workstation or transmitting/receiving device. The RCA 110 connectors utilize UTP cable (category 3, 5, 5e, 6, 6A) to deliver component/composite signals within a horizontal point-to-point run.

Hubbell's 110 RCA connectors deliver high quality A/V signals to any

RCA 110 connectors are available with 5 different insulator colors and snap into any **iSTATION**™ product, module, frame, surface housing, poke-through, raceway, delivery or even a UDX multimedia panel to distribute audio/video signal. Requiring no soldering, these connectors install with a snap.

Create a customized multimedia workstation by snapping a RCA 110 Connector along with HPW's extensive line of AV connectors, loaded modules and **XCELERATOR**™ jacks.

CABLE TERMINATION

Cable Type:

- 110 IDC's: 24 AWG UTP Cat 3, 5, 5e, 6, 6A.
- RCA: Male RCA Plug (patch cord).

APPLICATIONS SUPPORTED

- Composite/component audio/video distribution.
- TV, CCTV, CATV, satellite and home theater ane entertainment systems.
- Cameras, camcorders and projectors.
- Security and surveillance systems.


CONNECTOR TERM

RCA Connector - The standard connector used in line-level consumer and studio sound equipment. RCA connectors supply unbalanced signal and are used in almost all systems and between almost all audio/video components. They are used for interconnecting Composite, Component and Digital coaxial audio video signals.

INSTALLATION TIPS

Termination: Station side of connection is a 110 style punch down. Simply lace in 1 pair of UTP into the outer sides of the IDC block. For example, pair 1 (the blue pair) terminate the (1) blue conductor into the IDC located on the left side, (\cap) ground slot. Then insert the Blue/White conductor into the IDC located on the right side, (\bullet) signal slot.

NOTE: The key practice is to use the same pair/pairs on each side of the horizontal run. Also use the same pair color combinations for each application (Composite, Component, Left and Right Audio, 3.5mm and S-Video).



WORK STATION HUBBELL PREMISE WIRING

AV Connector, RCA 110-Style


Sold in carton increments only. Carton contains - 25 keystone connectors (individually bagged). Housing Color: Black.




XX = Insulator Color: "B" = Blue; "GN" = Green; "R" = Red; $\mathbf{W}^{"} = \mathbf{W}$ hite; $\mathbf{Y}^{"} = \mathbf{Y}$ ellow.

RCA INSULATOR COLOR: APPLICATIONS		
Color	Audio	Video
Red	Right Signal	Component - Red (Pr/Cr)
White	Left Signal	
Yellow		Composite
Blue		Component - Blue (Pb/Cb)
Green		Component - Green (Y)
Black	Mono/Right	
Orange	Digital (S/PDIF)	Digital (S/PDIF)

CONNECTOR DEPTH CHART



DIMENSIONS



iSTATION™ COMPATIBLE

Work Station and Cross-Connect Solutions

- Front and Rear-loading Plates
- Duplex and Decorator Frames
- ISM Surface Mount Boxes
- UDX Multimedia Panels (except 1U-48)
- NETSELECT® Residential Network Solution
- iFRAME® Vertical Patch Panel


Delivery System

- SystemOne Poke-Throughs and Floor Boxes
- Surface Raceway, Metal and Non-Metallic
- Multi-Connect[™] Wall Boxes/Conference Table Boxes
- Power Poles





TYPICAL APPLICATION



Worldwide Locations

Hubbell Premise Wiring, Asia Pacific Hubbell Canada Inc. Hubbell Premise Wiring, Central America Hubbell Premise Wiring, China Hubbell Premise Wiring, Europe Hubbell Premise Wiring, India Hubbell Int'l. Inc., Korea Branch

852-2836-7131 905-839-1138 506-309-4158 86-21-6374 2660 44-01283 500500 91-80-4022-4089 (82 2) 2607 1363

Fax: 852-2836-7132 Fax: 905-839-9108 Fax: 506-260-1616 Fax: 86-21-6374 2799 Fax: 44-01283 500400 Fax: 91-80-4022-4033

Fax: (82 2) 2603 7386

Fax: (860) 535-8328 • Internet site: http://www.hubbell-premise.com

Hubbell Premise Wiring, Latin America Hubbell de Mexico, S.A. de C.V. Hubbell Premise Wiring, Middle East Hubbell Premise Wiring, Puerto Rico Hubbell-Taian Co., Ltd., Taiwan Hubbell Premise Wiring, Venezuela

305-408-4501 (5255) 9151-9999 971-4-393-4192 787-855-1075 886-2-2522-1862

Fax: 305-408-8201 Fax: (5255) 9151-9989 Fax: 971-4-393-4194 Fax: 787-855-3265 Fax: 886-2-2522-1872 58-212-5156482 Fax: 58-212-6627258

DS-C46 2/08