

Rear load angled high density jack panel kit for 48 Clarity 6 or 5E panel jacks

OR-PHAPJU48



Rear load angled high density jack panel kit for 48 Clarity 6 or 5E panel jacks. It occupies 2 rack units and measures 19" x 3.5".

features & benefits

- Jacks rear load into panels: All terminations done from rear of panel.
- New positive jack latching design: Secure mounting of jacks into panel.



- Recessed design with lower mounted profile: Directs cords more easily to vertical management.
- High density solution: Maximizes rack space.
- Panel jacks support snap-in icons: Easy designation of ports.
- Universal wiring labels on panel jacks: Supports both T568B and T568A wiring schemes.
- Silkscreened 1-48: Easy port identification.

specifications

General Info

Category Performance Application: Category 6 or 5e when loaded with Category 6 or 5e panel jacks

Color: Black with blue silkscreen

Footprint: Clarity 6 or 5E rear load PJ series panel jacks

Mod Jack Wiring: Field defined Number Of Ports: Up to 48

Assembly/Installation Information

Installation Tips: Terminate panel jack and then rear load into the panel, maintaining minimum bend radius of four

times the cable diameter.

Mounting Hardware Included: Yes

Listing Agencies/Third Party Information

CUL Listing No: E131600 UL Listing No: E131600 UL Standard: Yes

Construction Information

Component1: Panel

Component2: Patch Panel Mounting Screws #12-24 x 5/8"

Finish Plating1: Black with blue silkscreen

Finish Plating2: Black Material1: .090 aluminum

Material2: Steel

Dimensions

Depth Metric: 38.86 mm Height Metric: 88.90 mm Height U S: 3.5 in Width Metric: 482.6 mm

Technical Information

Performance Rating: Category 6 or 5e, based on selection of panel jack

Buy American Act Compliance

Country of Origin: UNITED-STATES-OF-AMERICA Buy American Act Status: Buy American Act Compliant