Technical Data Sheet Plenum Communication Cables

WEST PENN WIRE



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

PART NUMBER: 253270B

DESCRIPTION: 22/6 Stranded bare copper conductors, shielded with an overall jacket.

NEC RATING: CMP, NEC Article 800

APPROVALS: (UL) C(UL) Listed or c(ETL)us Listed

APPLICATION: Indoor within ducts, plenums, and other spaces used for environmental air for (Intercom Systems,

Security Systems, Sound, Audio, Background Music)

Construction Parameters:

Conductor 22 AWG Bare Copper

Stranding 7x30

Insulation MaterialFlex Plenum PVCInsulation Thickness0.007" Nom.

Number of Conductors

Shield 100% Aluminum Polyester Foil
Drain Stranded Tinned Copper
Jacket Material Flex Plenum PVC
Jacket Thickness 0.015" Nom.
Overall Cable Diameter 0.162" Nom.

Flame Rating NFPA 262 Flame Test

Electrical & Environmental Properties:

Temperature Rating -10°C To +60°C
Operating Voltage 300 V RMS
Max.Capacitance Between Conductors @ 1 KHz 55 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz 99 pf/ft Nom.

DC Resistance per Conductor @ 20deg C 17 Ohms/1M' Nom.

Insulation Colors

Black, Red, White, Green, Brown, Blue
Jacket Color

RoHS Compliant

Gray, White
Yes

Mechanical Properties:

Max. Recommended Pull Tension
Min. Bend Radius (Install)

Specification Issue Date: 7/06

Approximate Cable Weight

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire 69 lbs 1.8"

25 Lbs/1M' Nom.



Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.