Technical Data Sheet Communication Cables

WEST PENN WIRE



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

PART NUMBER: 301

DESCRIPTION: 22/3 Stranded tinned copper conductors, shielded with an overall jacket

NEC RATING: CMR, NEC Article 800

APPROVALS: (UL) C(UL) Listed or c(ETL)us Listed

APPLICATION: Communications Cable for Riser

Construction Parameters:

Conductor 22 AWG Tinned Copper

Stranding 7x30
Insulation Material PVC
Insulation Thickness 0.007" Nom.

Number of Conductors

Shield 100% Aluminum Polyester Foil
Drain Stranded Tinned Copper

Jacket MaterialPVCJacket Thickness0.017" Nom.Overall Cable Diameter0.138" Nom.Approximate Cable Weight13.7 Lbs/1M' Nom.Flame RatingUL 1666 Riser Flame Test

Electrical & Environmental Properties:

Temperature Rating -20°C To +60°C Operating Voltage 300 V RMS Max.Capacitance Between Conductors @ 1 KHz 55 pf/ft Nom. Capacitance Between Conductors to Shield @ 1 KHz 99 pf/ft Nom.

DC Resistance per Conductor @ 20deg C 17 Ohms/1M' Nom.
Insulation Colors Black, Red, White

Jacket Color Gray
RoHS Compliant Yes

Mechanical Properties:

Max. Recommended Pull Tension
Min. Bend Radius (Install)

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire 46 lbs. 1.4"



Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.