

Self-Amplified Drop-In Ceiling Speaker

with back can and recessed
volume control



Models
ACD2X2, ACD2X2U



Description Bogen's ACD2X2 Drop-In Ceiling Speaker is a full-range, 1-watt, self-amplified speaker that is quick and easy to install. Simply wire it and drop it into place. Available in off-white (ACD2X2) and bright white (ACD2X2U).

The ACD2X2 is 2' x 2', designed to fit perfectly into place in 2' x 2' ceiling grids - without needing to cut ceiling tiles. The ACD2X2 can also be easily installed in 2' x 4' ceiling grids using the included support rail.

- Features**
- For use with both 2 ft. x 2 ft. and 2 ft. x 4 ft. suspended tile ceilings (support rail crossbar included for 2 ft. x 4 ft. suspended tile ceilings)
 - Finely perforated grille covers entire front of speaker
 - Fully enclosed, industrial grade steel construction
 - Self-contained 1-watt amplifier
 - 8" main cone speaker, with secondary cone
 - Front-mounted, recessed volume control
 - Non-reflective finish, available in off-white (ACD2X2) and bright white (ACD2X2U)
 - Seismic attachment points
 - Complies with UL-2043

Technical Specifications

Max. SPL: 94 dB (1m)
Frequency Response: 95 Hz - 12 kHz
Supply Voltage: 24V DC
Typical Current Units: 1 CU (50 mA)
Idle Current: 5 mA (nominal)
Input Sensitivity: 125 mVrms
Input Impedance: 2k ohms

Dispersion: 100°
Cone: 8" cone speaker, with secondary cone
Magnet Weight: 10 oz.
Connection: Wire leads via wire nuts (*included*)
Dimensions: 23-7/8" W x 5" H x 23-7/8" D
Product Weight: 12 lb.

Architect and Engineer Specifications The speaker shall be a Bogen Model ACD2X2 (or ACD2X2U) Drop-In Self-Amplified Ceiling Speaker, which shall be fully enclosed and constructed of industrial grade steel. It shall be comprised of a damped high-compliance factory-mounted 8" loudspeaker that shall consist of an 8" treated paper cone and a 10-ounce magnet, including a secondary cone.

The unit shall have a 1-watt amplifier. The typical current consumption shall be 1 CU (50 mA). Frequency response shall be 95 Hz - 12 kHz. Input sensitivity shall be 125 mVrms. Input impedance shall be 2k ohms. Dispersion shall be 100°.

The speaker shall have a non-reflective, off-white (or bright white for ACD2X2U) metal finish grille with a recessed volume control accessible through front grille. It shall include 4 seismic attachment points.

The speaker assembly will fit into 2' x 2' and 2' x 4' ceiling tiles. For 2' x 2' installations, a support rail shall not be needed and no cuts to the ceiling shall be necessary. For 2' x 4' installations, a single cut to the ceiling tile and an included support rail shall be needed.

The speaker shall measure 23-7/8" W x 5" H x 23-7/8" D and shall weigh 12 lb.

BOGEN®
COMMUNICATIONS, INC.

50 Spring Street, Ramsey, NJ 07446, U.S.A.
Tel: 201-934-8500, Fax: 201-934-9832, Web Site: www.bogen.com