

ROCKETLINX ES8510-XT

Industrial Ethernet Switch

HIGHLIGHTS

- Multiple redundant ring (recovery time <5ms)
- 7 10/100BASE-TX ports and 3 Gigabit RJ45/SFP combo ports (10/100/1000BASE-TX, 100BASE-FX, 1000BASE-X)
- 32Gbps non-blocking, 8K MAC address table
- VLAN, GVRP, QoS, IGMP snooping V1/V2/V3, rate control, port trunking, LACP, online multi-port mirroring
- Management via console CLI, Web, SNMP V1/V2c/V3, RMON, HTTPS, SSH and NetVision
- Advanced security feature supports IP security, port security, DHCP server, IP and MAC binding, 802.1x network access control
- Event notification by email, SNMP trap, syslog, digital input and relay output
- -40° to +74° C operating temperature for extreme environments
- Rigid aluminum IP31 housing, excellent heat dispersion, redundant power, DIN Rail/wall-mount installation
- NEMA TS2 compliant



Part Number
32061-6



Extreme Temperature Ratings
-40°C to +74°C



Product Description

The RocketLinx ES8510-XT is a managed Industrial Ethernet Switch, equipped with seven 10/100TX ports and three 10/100/1000 RJ45/100-FX/Gigabit SX/LX/LHX/ZX/SFP combo ports. Two gigabit ports may be used to form a non-stop Redundant Ring while the third gigabit port enables connection to an upper switch, couple ring or public server. The Gigabit combo port design provides flexibility to choose copper or fiber media supporting 100BASE-FX or 1000BASE-X, Multi-Mode or Single-Mode for a wide variety of distance and installation requirements.

The RocketLinx ES8510-XT is housed in a rugged aluminum enclosure that features an excellent heat dispersing mechanical design and a wide operating temperature support. The embedded software supports full Layer 2 management features, multi-form ring redundancy, network control, monitoring, security and notification. The RocketLinx ES8510-XT also provides a built-in watchdog timer and digital input and relay output to avoid undetected problems. The RocketLinx ES8510-XT provides the perfect foundation for building your industrial Ethernet infrastructure.

Three Gigabit Ports for Flexible Network Planning

A unique feature to the RocketLinx ES8510-XT is the three Gigabit RJ45/SFP combo ports, which can improve performance dramatically compared to products with only two Gigabit RJ45/SFP combos. Each combo comes with a flexible connection -- 100Mbps or 1000Mbps, as well as fiber or copper connection options. All together, as many as ten different combinations of port connections are possible. By selecting the appropriate fiber transceivers, the RocketLinx ES8510-XT can meet your industrial application requirements with virtually any transmission distance.

100/1000Mbps SFP

The RocketLinx ES8510-XT SFP socket supports 100BASE-FX Single/Multi-Mode and 1000BASE-SX/LX/LHX/XD Multi/Single Mode transceivers. The available distance of the 100BASE-FX is up to 30KM. 1000BASE-SX Multi-Mode supports 550M, 1000BASE-LX Single-Mode supports 10KM, 1000BASE-LHX Single-Mode supports 30KM, 1000BASE-XD Single-Mode supports up to 50KM. 1000BASE-ZX Single-Mode supports up to 70KM.



SPECIFICATIONS

HARDWARE

Bus Interface Specification	10/100/1000BASE-TX; 100BASE-FX; 1000BASE-SX/LX/LHX/XD/ZX Gigabit Fiber
Enclosure	IP31 Grade Aluminum;
Installation Method	DIN-Rail
LED Indicators	Power 1, Power 2, Ring Master (R.M.); 10/100BASE-TX Link/ Activity 10/100BASE-TX Full-Duplex/Collision; Gigabit Copper/ SFP Link/Activity; Digital Input 1 & 2, Digital Output 1 & 2
Dimensions	5.0" x 6.3" x 3.7"
Product Weight	2.63 lb

TECHNOLOGY

Standards	
IEEE 802.3	10BASE-T
IEEE 802.3u	100BASE-TX and 100BASE-FX
IEEE 802.3AB	1000BASE-TX
IEEE 802.3z	Gigabit Ethernet Fiber
IEEE 802.1D-2004	Rapid Spanning Tree Protocol (RSTP)
IEEE 802.1Q-2003	VLAN Tagging and GVRP
IEEE 802.1p	Class of Service
IEEE 802.3ad	For Port Trunk with Link Aggregation Control Protocol (LACP)
IEEE802.1X	Port Based Network Access Control
IEEE802.3x	Flow Control and Back-Pressure

PERFORMANCE

Switch Technology	32Gbps Switch Fabric Store and Forward Switch Technology
System Throughput	14,880pps for 10Mbps; 148,800pps for 100Mbps; 1,488,100 for Gigabit Ethernet
Number of MAC Address	8K
Packet Buffer Memory	1Mbits
Transfer Packet Size	64 bytes to 1522 bytes (with VLAN Tag)
Priority Queues per Port	4
Port Trunk (Max)	5 Static Trunk
VLAN (Max)	64
DHCP Server	Up to 255 IP Addresses

MANAGEMENT FEATURES

Configuration	Cisco compatible CLI, NetVision Utility, HTTP, HTTPS, SSH, TFTP/Web update for firmware and configuration backup/ restore, DHCP Client, Warm reboot, Reset to default, Admin password, Port speed/duplex control, Status, Statistic, MAC address table display, Static MAC, Aging time, SNMP v1, v2c, v3, Traps and RMON1
SNMP MIB	MIB-II, Bridge MIB, VLAN MIB, SNMP MIB, RMON and Private MIB
Port Trunk	Up to 5 static trunk and IEEE 802.3ad LACP
VLAN	IEEE 802.1Q VLAN, GVRP. Up to 64 VLAN groups
Quality of Service (QoS)	Four priority queues per port, IEEE 802.1p COS and Layer 3 TOS/DiffServ
IGMP Snooping	IGMP Snooping V1/V2/V3 for multicast filtering and IGMP Query V1/V2
Rate Control	Ingress filtering for broadcast, multicast, unknown DA or all packets, and egress filtering for all packets
NTP	Network Time Protocol to synchronize time from Internet or local PC
Embedded Watchdog	Embedded hardware watchdog timer to auto reset system when switch system failure
Port Mirroring	Online traffic monitoring on multiple selected ports
Port Security	Assign authorized MAC to specific port

IP Security

IP security to prevent unauthorized access	
802.1x	Port-based network access control
DHCP Server	Up to 255 IP address, support IP and MAC binding
Email Warning	Automatic warning by pre-defined events
System Log	Supports both local mode and server mode

NETWORK REDUNDANCY

Rapid Spanning Tree Protocol	IEEE 802.1D-2004 rapid spanning tree protocol (RSTP) Compatible with Legacy STP and IEEE 802.1w
Redundant Ring Technology	Failure recovery within 5ms.
Rapid Dual Homing	Multiple uplink paths to upper switches
Redundant Ring	Rapid Spanning Tree VLAN Tagging and Super Ring IEEE

ELECTRICAL SPECIFICATIONS

Device	
DC Input Voltage	12-48VDC
Current Consumption	
+24VDC	0.8A
Power Consumption (Max)	20W
Power Connector	1
Power Connector Type	4-Pin Screw Terminal Block
Power Input Redundancy	Dual Redundant Independent Power Inputs
Reverse Polarity Protection	Yes
Power Alarm Relay	Alarm for power failure notification
Relay Rating	1A Max @ 24VDC

ENVIRONMENTAL

Air Temperature	
System On	-40° to +74° C
System Off	-40° to +74° C
Operating Humidity	
Non-condensing	5% to 95%
MTBF (Mean Time Between Failures)	28.53 years

ETHERNET SPECIFICATIONS

Connector Type	RJ45
Number of Port	10
Ethernet Cable Type	CAT-3, CAT-4, CAT-5, CAT-5e (UTP or STP)
Standard for RJ45 Ports	(7) 10/100BASE-TX Auto MDI/MDIX, Auto Negotiation (3) 10/100/1000BASE-TX, Combo with SFP
Standard for Optional SFP	1000BASE-SX/LX/LHX/ XD/ZX Gigabit Fiber
Port Alarm Relay	100BASE-FX Alarm Relay for Port Failure Notification
Relay Rating	1A Max. @ 24VDC

SERIAL CONSOLE PORT SPECIFICATION

Connector Type	RJ45
Number of Port	1
Serial Interface	RS-232 (TXD, RXD, Signal GND)
Baud Rate	9600bps
Device Data Control	
Data Bits	8
Parity	None
Stop Bits	1
Flow Control	None

DIGITAL INPUT SPECIFICATION

Connector Type	4-Pin screw Terminal Block
Number of Inputs	2 Sets
Voltage Levels	
Logic Low (0)	0 to 10VDC

DIGITAL OUTPUT SPECIFICATION

Connector Type	4-Pin Screw Terminal Block
Number of Outputs	2 Sets of Relay Outputs
Output Relay Rating	1A Max. @ 24VDC

EXPORT INFORMATION

Packaged Shipping Weight	3.9 lbs
Package Dimensions	11.3" x 5.5" x 9.1"
UPC Code	7-56727-32061-6
ECCN	5A991
Schedule B Number	8517.62.0050

REGULATORY APPROVALS

Emissions	Canadian EMC Requirements ICES-003
European Standard EN55022	
CISPR 22	
FCC Part 15 Subpart B	Class A limit
Immunity	European Standard EN55024 IEC 1000-4-2/EN61000-4-2: ESD IEC 1000-4-3/EN61000-4-3: RF IEC 1000-4-4/EN61000-4-4: Fast Transient IEC 1000-4-5/EN61000-4-5: Surge IEC 1000-4-6/EN61000-4-6: Conducted Disturbance IEC 1000-4-8/EN61000-4-8: Magnetic Field IEC 1000-4-11/EN61000-4-11: Dips and Voltage Variations
Safety	IEC 60950/EN60950 (LISTED) CSA C22.2 No. 60950/UL60950 Third Edition
Other	European Standard: 2002/95/EC Directive (RoHS) NEMA TS2 Compliant
Regulatory Approvals	RoHS 2002/95/EC CE FCC UL/cUL



ORDERING INFORMATION

32061-6 RocketLinx ES8510-XT

RECOMMENDED ACCESSORIES

32101-9	PS1060, 60 Watts Industrial DIN Rail Power Supply (24V, 60W, DIN Rail)
32102-6	PS1100, 100 Watts Industrial DIN Rail Power Supply (24V, 100W, DIN Rail)
1200038	24VDC External Power Adapter, Bare Wires (24VDC, 24W, 3-Wire)

PRODUCT SUPPORT & SERVICE INFORMATION

Warranty Information

Control offers a 30-day satisfaction
guarantee and 5-year limited warranty.

Sales Support

+1.763.957.6000
sales@control.com

Technical Support

+1.763.957.6000
www.control.com/support

Email, FTP, and Web Support

info@control.com
ftp.control.com
www.control.com