



STS3-12

Three-way Snap-in Stand-off Adapter for 1–2 in round members

Dimensions

Compatible Diameter, maximum	50.800 mm		2.000 in
Compatible Diameter, minimum	25.400 mm		1.000 in
Outside Length	1975.10 mm		77.76 in
Outside Width	1012.44 mm		39.86 in

General Specifications

Adapter Type	Adapter
Material Type	Stainless steel
Package Quantity	10

Mechanical Specifications

Material Thickness	2.591 mm		0.102 in
Maximum Loading	Double stack, 1-5/8 in cable		
Mounting	3/4 in through hole		

Packed Dimensions

Height	12.0 cm		4.7 in
Length	1.0 cm		0.4 in
Shipping Weight	0.58 kg		1.28 lb
Width	11.0 cm		4.3 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

Included Products

31670-1 — Round Member Adapter for 1–2 in round members

SA-38 — Universal Stand-off Adapter

TTS3-34 — Three-way Stand-off Adapter for 3–4 in round members

- UAAI — Universal Angle Adapter Insert
- 31670-3 — Round Member Adapter for 3–4 in round members
- SA-38 — Universal Stand-off Adapter

TTS3-45 — Three-way Stand-off Adapter for 4–5 in round members

- UAAI — Universal Angle Adapter Insert
- SA-38 — Universal Stand-off Adapter
- 31670-4 — Round Member Adapter for 4–5 in round members

STS3-12



TTS3-56 — Three-way Stand-off Adapter for 5–6 in round members

- UAAI — Universal Angle Adapter Insert
- SA-38 — Universal Stand-off Adapter
- 31670-5 — Round Member Adapter for 5–6 in round members

TTS3-153 — Three-way Stand-off Adapter for 1.5–3 in round members

- UAAI — Universal Angle Adapter Insert
- SA-38 — Universal Stand-off Adapter
- 31670-2 — Round Member Adapter for 2–3 in round members

TTS3-7515 — Three-way Stand-off Adapter for 0.75–1.5 in round members

- UAAI — Universal Angle Adapter Insert
- SA-38 — Universal Stand-off Adapter
- 31670-1 — Round Member Adapter for 1–2 in round members