


760154757 | Z-006-LN-8W-F06BK/25D

Indoor/Outdoor Low Smoke Zero Halogen Single Jacket All-Dielectric Stranded Loose Tube Arid Core® Cable

Representative Image



General Specifications

Cable Type	Stranded loose tube
Construction Type	Non-armored
Subunit Type	Gel-free

Construction Materials

Fiber Type Solution	TeraSPEED®, zero water peak singlemode fiber
Total Fiber Quantity	6
Fiber Type	TeraSPEED®, zero water peak singlemode fiber
Fiber Type, quantity	6
Fibers Per Subunit, quantity	6
Jacket Color	Black
Jacket UV Resistance	UV stabilized

Dimensions

Buffer Tube/Subunit Diameter	2.50 mm 0.10 in
Cable Weight	125.0 kg/km 84.0 lb/kft
Diameter Over Jacket	11.70 mm 0.46 in
Filler, quantity	4
Subunit, quantity	1

Physical Specifications

Minimum Bend Radius, loaded	17.5 cm 6.9 in
-----------------------------	------------------

760154757 | Z-006-LN-8W-F06BK/25D

Minimum Bend Radius, unloaded	11.7 cm		4.6 in
Tensile Load, long term, maximum	180 lbf		800 N
Tensile Load, short term, maximum	2700 N		607 lbf
Vertical Rise, maximum	654.0 m		2145.7 ft

Flame Test Specifications

Flame Test Listing	NEC OFN-LS (ETL) and c(ETL)		
Flame Test Method	CSA FT4	IEC 60332-3	IEC 60754-2 IEC 61034-2 IEEE 1202 IEEE 383 NES 713 UL 1685

Environmental Specifications

Environmental Space	Aerial, lashed	Buried	Low Smoke Zero Halogen (LSZH)	Riser
Installation Temperature	-30 °C to +70 °C (-22 °F to +158 °F)			
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)			
Storage Temperature	-40 °C to +75 °C (-40 °F to +167 °F)			

Mechanical Test Specifications

Compression	125 lb/in		22 N/mm
Compression Test Method	FOTP-41		IEC 60794-1-2, Section 7
Flex	35 cycles		
Flex Test Method	FOTP-24		IEC 60794-1-2, Section 10
Impact	2.21 ft lb		3.00 N-m
Impact Test Method	FOTP-25		IEC 60794-1-2, Section 8
Strain	See long and short term tensile loads		
Strain Test Method	FOTP-33		IEC 60794-1-2, Section 5
Twist	10 cycles		
Twist Test Method	FOTP-85		IEC 60794-1-2, Section 11
Water Penetration	24 h		
Water Penetration Test Method	FOTP-82		IEC 60794-1-2, Section 24

Environmental Test Specifications

Cable Freeze	-2 °C		28 °F
Cable Freeze Test Method	FOTP-98		
Drip	70 °C		158 °F
Drip Test Method	FOTP-81		IEC 60794-1-2, Section 17
Heat Age	-40 °C to +85 °C (-40 °F to +185 °F)		
Heat Age Test Method	Not applicable		
Low High Bend	-30 °C to +60 °C (-22 °F to +140 °F)		
Low High Bend Test Method	FOTP-28		IEC 60794-1-2, Section 28
Temperature Cycle	-40 °C to +70 °C (-40 °F to +158 °F)		
Temperature Cycle Test Method	FOTP-3		IEC 60794-1-2, Section 22

Qualification Specifications

Cable Qualification Standards	ANSI/ICEA S-104-696-2001 EN 187105 Telcordia GR -20-CORE Issue 3 Telcordia GR-409-CORE Issue 2		
-------------------------------	--	--	--

760154757 | Z-006-LN-8W-F06BK/25D

Regulatory Compliance/Certifications

Agency

RoHS 2002/95/EC
ISO 9001:2008

Classification

Compliant
Designed, manufactured and/or distributed under this quality management system



Included Products

CS-8W-IOLT (Product Component—not orderable) — TeraSPEED® OS2 Singlemode Fiber