Product Specifications





UC1AAA2-08 | UNC10G-WH

Uniprise Ultra 10® Category 6A U/UTP Patch Cord, Snagless, White Jacket

Dimensions

Cord Length, maximum 100 ft | 30 m Cord Length, minimum 7 ft | 2 m

Electrical Specifications

ANSI/TIA Category 6A dc Resistance, maximum 0.30 ohm Safety Voltage Rating 300 V

Environmental Specifications

Environmental Space Non-plenum Flammability Rating UL 94 V-0

Operating Temperature $-10 \, ^{\circ}\text{C}$ to $+60 \, ^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +140 $^{\circ}\text{F}$)

Safety Standard CETL | ETL

General Specifications

Cable Type U/UTP (unshielded)

Interface, connector A RJ45 plug
Interface, connector B RJ45 plug
Jacket Color White

Brand Ultra 10® | Uniprise®

Interface Feature, connector A Standard Interface Feature, connector B Standard

Package, quantity 1
Pairs, quantity 4

Mechanical Specifications

Conductor Type Solid

Material Type Copper alloy | Polycarbonate

Outlet/Module Contact Plating Precious metals
Plug Insertion Life, minimum 750 times
Plug Retention Force, minimum 133 N | 30 lbf

Wiring T568B

Wiring Diagram

Product Specifications



UC1AAA2-08 | UNC10G-WH

	Connector A	Connector B
Position 1	White/Orange	White/Orange
Position 2	Orange	Orange
Position 3	Lt. Green	Lt. Green
Position 4	Blue	Blue
Position 5	Lt. Blue	Lt. Blue
Position 6	Green	Green
Position 7	Lt. Brown	Lt. Brown
Position 8	Brown	Brown

Regulatory Compliance/Certifications

Agency RoHS 2002/95/EC **Classification**Compliant

ISO 9001:2008

Designed, manufactured and/or distributed under this quality management system



Included Products

CC8469444 | UNC10G WHITE 4/24 Bulk (Product Component—not orderable) — Ultra 10® 10GNJ4 Category 6A U/UTP Cable, non-plenum, white jacket, 4 pair count, bulk length, reel