






Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Han® HC Modular 350 Crimp terminal 	09 11 001 3001	09 11 001 3101		

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm																		
		Male contact	Female contact																				
Crimp contacts* silver plated																							
	35	09 11 000 6140	09 11 000 6240																				
	50	09 11 000 6141	09 11 000 6241																				
	70	09 11 000 6142	09 11 000 6242																				
	95	09 11 000 6143	09 11 000 6243																				
	120	09 11 000 6144	09 11 000 6244																				
					<table><tr><th>Wire gauge</th><th>Ø</th><th>Stripping length</th></tr><tr><td>35 mm²</td><td>8,2</td><td>26 mm</td></tr><tr><td>50 mm²</td><td>10</td><td>28 mm</td></tr><tr><td>70 mm²</td><td>11,5</td><td>28 mm</td></tr><tr><td>95 mm²</td><td>13,5</td><td>30 mm</td></tr><tr><td>120 mm²</td><td>15,5</td><td>24 mm</td></tr></table>	Wire gauge	Ø	Stripping length	35 mm²	8,2	26 mm	50 mm²	10	28 mm	70 mm²	11,5	28 mm	95 mm²	13,5	30 mm	120 mm²	15,5	24 mm
Wire gauge	Ø	Stripping length																					
35 mm²	8,2	26 mm																					
50 mm²	10	28 mm																					
70 mm²	11,5	28 mm																					
95 mm²	13,5	30 mm																					
120 mm²	15,5	24 mm																					
for stranded wire according to IEC 60 228 Class 5																							

* Crimp zone acc. to EN 46 235

Stock items in bold type