



Number of contacts

2



Identification	Part-Number		Drawings	Dimensions in mm
	Male insert (M)	Female insert (F)		
Han® 70 A module Crimp terminal	09 14 002 3041	09 14 002 3141		

Han
Modular

Identification	Wire gauge mm ²	Part-Number		Drawings	Dimensions in mm												
		Male contacts (M)	Female contacts (F)														
Crimp contacts*																	
Silver plated																	
	10	09 11 000 6131	09 11 000 6231														
	16	09 11 000 6132	09 11 000 6232														
	25	09 11 000 6133	09 11 000 6233														
<table><tr><th>Wire gauge</th><th>Ø</th><th>Stripping length</th></tr><tr><td>10 mm²</td><td>4.3</td><td>15.5 mm</td></tr><tr><td>16 mm²</td><td>5.5</td><td>15.5 mm</td></tr><tr><td>25 mm²</td><td>7.0</td><td>15.5 mm</td></tr></table> for stranded wires acc. to IEC 60 228 class 5						Wire gauge	Ø	Stripping length	10 mm ²	4.3	15.5 mm	16 mm ²	5.5	15.5 mm	25 mm ²	7.0	15.5 mm
Wire gauge	Ø	Stripping length															
10 mm ²	4.3	15.5 mm															
16 mm ²	5.5	15.5 mm															
25 mm ²	7.0	15.5 mm															

* Crimp zone acc. to DIN EN 46 235