

## Product information G 4 A 5 M grau/grey

Industrial Connecting Solutions:Rectangular Connectors:DIN VDE 0627 / IEC 61984 Connectors (G serie):Cable plug:G 4 A 5 M grau/grey

G 4 A 5 M grau/grey

http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24347-24349-36967/en/conf/uistate/link/stat

|                                   | Surface mounted connector for printed circuit boards with flange and solder contacts   |  |
|-----------------------------------|--|--|
| Delivery informations             | • • • • • • • • • • • • • • • • • • •  |  |
| Availability                      | available  |  |
| Product description               |  |  |
| Description                       | Surface mounted connector for printed circuit boards with flange and solder contacts   |  |
| Туре                              | G 4 A 5 M graw/grey  |  |
| Order No.                         | 932 092-106  |  |
| Type of contact                   | blade contacts   |  |
| Number of contacts                | 4  |  |
| Standard                          | DIN VDE 0627 / IEC 61984   |  |
| Housing Color                     | grey   |  |
| Technical data                    |  |  |
| Pin dimensions                    | 2.8 mm x 0.8 mm  |  |
| Rated voltage                     | AC/DC 50 V   |  |
| Rated current                     | 10 A   |  |
| Contact resistance                | <= 4 m0hm  |  |
| Type of termination               | solder (solder tabs for printed circuits)  |  |
| Mounting                          | screws   |  |
| Material                          |  |  |
| Contact surface material          | Sn   |  |
| Contact bearer material           | PA PA  |  |
| Housing material                  | PA PA  |  |
| <b>Environmental conditions</b>   |  |  |
| Protection class (IEC 60529)      | IP 65  |  |
| Pollution severity                | 3  |  |
| Temperature range                 | -40 °C to +90 °C   |  |
| Inflammability class              |  |  |
| Housing                           | 94 HB  |  |
| Contact bearer                    | 94 HB  |  |
| Approvals                         |  |  |
| VDE                               | VDE  |  |
| Packing unit                      | Land to  |  |
| Packaging unit                    | 100 pieces   |  |
| Scope of delivery and accessories | A wife and the second s |  |
| Scope of delivery                 | 1 surface mounted connector  |  |
| Accessories to order separately   | can be plugged into G 4 W 1 F grau, G 4 KW 1 F 2m; flat gasket G 30 E-2, order no. 733 415-002   |  |






Industrial Connecting Solutions:Rectangular Connectors:DIN VDE 0627 / IEC 61984 Connectors (G serie):Cable plug:G 4 A 5 M grau/grey

http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24347-24349-36967/en/conf/uistate

Picture

Drawing



## Belden Deutschland GmbH

lm Gewerbepark 2 58579 Schalksmühle

Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

