



HIRSCHMANN

A BELDEN BRAND

Product information ELST 5012 PG9

Industrial Connecting Solutions: Circular Connectors: M8 - M12 Connectors: M12 Connectors: M12 Circular connector (M12 E-Series): with screw locking: Straight cable plug, self-assembled: ELST 5012 PG9

<http://www.e-catalog.beldensolutions.com/link/57078-24228-256281-256292-256304-24445-24446-24271-36766/en/conf/ui.state>

Name		ELST 5012 PG9
		
		Straight cable plug, unassembled, strain relief by means of clamping cage
Delivery informations		
Availability		available
Product description		
Description		Straight cable plug, unassembled, strain relief by means of clamping cage
Type		ELST 5012 PG9
Order No.		933 164-100
Type of contact		male
Number of contacts		5
Cable gland		PG 9
Standard		IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2
Housing Color		black
Technical data		
Pin dimensions		1 mm
Rated voltage		AC/DC 50 V
Rated current		4 A
Type of termination		screw
Suitable cables		diameter 6 mm to 8 mm, max. 0.75 mm ²
Material		
Contact material		Cu Zn
Contact surface material		Sn
Contact bearer material		PA
Housing material		PA
Coupling nut material		Zn Al/Ni
O-Ring		NBR
Environmental conditions		
Protection class (IEC 60529)		IP 67
Pollution severity		3
Temperature range		-25 °C to +90 °C
Inflammability class		
Housing		94 V-2
Contact bearer		94 V-2
Packing unit		
Packaging unit		100 pieces

Industrial Connecting Solutions: Circular Connectors: M8 - M12 Connectors: M12 Connectors: M12 Circular connector (M12 E-Series)-with screw locking: Straight cable plug, self-assembled: ELST 5012 P69
<http://www.e-catalog.beldensolutions.com/link/57078-24228-256281-256292-256304-24445-24446-24271-36766/en/conf/ui.state>

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.