

## Product information

### ELST 4008 V

Industrial Connecting Solutions: Circular Connectors: M8 - M12 Connectors: M8 Connectors: M8 Connectors (E series M8): MiniQuick, fast connection, cable plug self-assembled: ELST 4008 V


<http://www.e-catalog.beldensolutions.com/link/57078-24228-256281-256292-256303-276518-24247-37238/en/conf/uistate>

| Name                                                                              |                                                                           |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| ELST 4008 V                                                                       |                                                                           |
|  |                                                                           |
| Straight cable plug, unassembled, strain relief by means of clamping cage         |                                                                           |
| Delivery informations                                                             |                                                                           |
| Availability                                                                      | available                                                                 |
| Product description                                                               |                                                                           |
| Description                                                                       | Straight cable plug, unassembled, strain relief by means of clamping cage |
| Type                                                                              | ELST 4008 V                                                               |
| Order No.                                                                         | 933 407-100                                                               |
| Type of contact                                                                   | male                                                                      |
| Number of contacts                                                                | 4                                                                         |
| Cable gland                                                                       | M 9.5 x 1                                                                 |
| Standard                                                                          | IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2                                    |
| Housing Color                                                                     | black                                                                     |
| Technical data                                                                    |                                                                           |
| Pin dimensions                                                                    | 1 mm                                                                      |
| Rated voltage                                                                     | AC/DC 20 V                                                                |
| Rated current                                                                     | 3 A (2 A at 0.14 mm <sup>2</sup> )                                        |
| Type of termination                                                               | pin penetration                                                           |
| Suitable cables                                                                   | diameter 4 mm to 5 mm / 0.14 mm <sup>2</sup> to 0.34 mm <sup>2</sup>      |
| Core insulation of connecting leads                                               | PVC, PETP, diameter 1.0 mm to 1.55 mm                                     |
| Material                                                                          |                                                                           |
| Contact material                                                                  | Cu Zn                                                                     |
| Contact surface material                                                          | Au                                                                        |
| Contact bearer material                                                           | PA                                                                        |
| Housing material                                                                  | PA                                                                        |
| Coupling nut material                                                             | Zn Al/Ni                                                                  |
| O-Ring                                                                            | Viton / NBR                                                               |
| Environmental conditions                                                          |                                                                           |
| Protection class (IEC 60529)                                                      | IP 67                                                                     |
| Pollution severity                                                                | 3                                                                         |
| Temperature range                                                                 | -25 °C to +70 °C                                                          |
| Inflammability class                                                              |                                                                           |
| Housing                                                                           | 94 V-2                                                                    |
| Contact bearer                                                                    | 94 V-2                                                                    |
| Packing unit                                                                      |                                                                           |
| Packaging unit                                                                    | 100 pieces                                                                |

Industrial Connecting Solutions: Circular Connectors: M8 - M12 Connectors: M8 Connectors: M8 Connectors (E series M8): MiniQuick, fast connection, cable plug self-assembled: ELST 4008 V  
<http://www.e-catalog.beldensolutions.com/link/57078-24228-256281-256292-256303-276518-24247-37238/en/conf/ui.state>

Picture

Drawing



**Belden Deutschland GmbH**

Im Gewerbepark 2  
58579 Schalksmühle  
Germany  
Phone: +49 7127/14-1806  
E-Mail: [icos-sales@belden.com](mailto:icos-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.  
The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.