

Product information GDML 2016 LED 24 HH grau/grey

Industrial Connecting Solutions: Archive - Industrial Connectors: Rectangular connectors GDM-series (Archive): Type A EN 175301-803 (DIN 43650) / ISO 4400: Cable socket with electronic insert: GDML

2016 LED 24 HH grau/grey

Name

http://www.e-catalog.beldensolutions.com/link/57078-24228-62529-86162-24310-24314-35625/en/conf/uistate

GDML 2016 LED 24 HH grau/grey

		1

	function indicator (LED) with protective circuit (diode)	
Delivery informations		
Availability	available	
Product description		
Description	function indicator (LED) with protective circuit (diode)	
Туре	GDML 2016 LED 24 HH grau/grey	
Order No.	934 415-003	
Other standard types	transparent housing, cable gland black: Order no. 934 415-002	
Number of contacts	2 + PE	
Cable gland	M 16 (grey)	
Conductor size	max. 1.5 mm ²	
Standard	DIN EN 175 301-803-A	
Housing Color	transparent	
Construction type	A	
Description of Wiring		
LED color	LED red	
Suppressor	diode	
Other characteristics	correct polarity must be ensured	
Technical data		
Pin dimensions	6.3 mm x 0.8 mm, 4.8 mm x 0.8 mm	
Rated voltage	DC 24 V	
Rated current	8A	
Contact resistance	<= 4 m0hm	
Type of termination	screw	
Suitable cables	4.5 mm to 10 mm diameter	
Mounting	central nut	
Material		
Contact surface material	Sn	
Contact bearer material	PA	
Housing material	PA	
Environmental conditions		
Protection class (IEC 60529)	IP 65 (gasket necessary)	
Pollution severity	3	
Temperature range	-40 °C to +90 °C	
Inflammability class		
Housing	94 HB	
Contact bearer	94 HB	
Packing unit		
Packaging unit	50 pieces	
Scope of delivery and accessories		
	4 M M M M M M M M M M M M M M M M M M M	

BELDEN

(NBR) flat gasket GDM 3-7, Order no. 730 801-002; (EPDM) flat gasket GDM 3-21, Order no. 731 739-004; profiled gasket GDM 3-16, Order no. 731 531-002;

Accessories to order separately

knurled screw GDM 3011-8, Order no. 732 574-001; stainless steel screw GDM 3011 RF-1, Order no. 734 363-001




Industrial Connecting Solutions:Archive - Industrial Connectors:Rectangular connectors GDM-series (Archive):Type A EN 175301-803 (DIN 43650) / ISO 4400:Cable socket with electronic insert:GDML 2016 LED 24 HH grau/grey

http://www.e-catalog.beldensolutions.com/link/57078-24228-62529-86162-24310-24314-35625/en/conf/uistate

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2 58579 Schalksmühle Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

