



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SR4POST

45U 4-Post SmartRack Open Frame Rack - Organize and Secure Network Rack Equipment



Highlights

- 45U 4-post open frame rack
- Black steel with square, numbered mounting holes
- Toolless button holes to accept PDUs or cable managers

Description

SmartRack 4-post open frame racks are ideal for cost conscious 19 inch rack mount applications. Multiple units can be bolted together side by side.

Package Includes

- SR4POST
- Installation hardware
- 50x pieces of M6 cage nuts, screws, and washers for equipment mounting
- Cable management hooks
- Owner's manual with warranty information

Features

- Supports 1000lbs of rackmount equipment
- Adjustable mounting depth (22 to 39 inches)
- Textured powder coat finish
- Heavy-duty cold-rolled steel construction
- Numbered mounting positions
- Bolt down provisions
- Self squaring design
- Includes mounting hardware of 50 pieces of M6 cage nuts, 50 pieces of M6 screws, and washers
- Black finish
- Easy assembly

Specifications

| PHYSICAL | |
|--|-------|
| Installed whole system maximum rack depth (inches) | 39.3 |
| Installed whole system maximum rack depth (cm) | 99.82 |

| | |
|--|--|
| Installed whole system minimum rack depth (inches) | 22.3 |
| Installed whole system total rack space height (rack spaces) | 45U |
| Shipping weight (lbs) | 55 |
| Shipping weight (kg) | 24.75 |
| Shipping Dimensions (HWD/in) | 6 x 4 x 85 |
| Shipping Dimensions (HWD/cm) | 15.24 x 10.16 x 216 |
| Unit weight (lbs) | 54 |
| Unit weight (kg) | 24.3 |
| Unit Dimensions (cm) | 214.12 x 51.3 x 55.9~99.1 (depth adjustable) |
| Unit Dimensions (in) | 84.3 x 20.2 x 22~39.3 (depth adjustable) |
| Color | Black |
| Weight Capacity - Stationary (lbs) | 1000 |
| Installed whole system minimum rack depth (cm) | 56.642 |
| Weight Capacity - Stationary (kg) | 453.6 |
| SPECIAL FEATURES | |
| Grounding lug | Includes screws, washers, and bolts to secure user-supplied grounding wire to front or back frames |
| CERTIFICATIONS | |
| NOM (Mexico) | Tested to NOM (Mexico) |
| Approvals | EIA-310-D, IEC 60297-3-100, DIN 41494, RoHS |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 5-year limited warranty |

Related Items

Optional Products

| Related Model | Description | Qty. |
|--------------------------------|--|------|
| B020-U08-19-IP | Console KVM Switch - 8-Port NetDirector 1U Rackmount Console IP KVM Switch w/17" LCD | 1 |
| B021-000-17 | Rackmount Console - 1U Rackmount Console with 17" LCD | 1 |
| B021-000-19 | Rackmount Console - 1U Rackmount Console with 19" LCD | 1 |
| B040-008-19 | NetController 19" VGA Console KVM Switch - 8 Port | 1 |
| B040-016-19 | NetController 19" VGA Console KVM Switch - 16 Port | 1 |
| N252-012 | 12-Port Cat6 Patch Panel 568B | 1 |

| | | |
|----------------|---|---|
| N252-024 | 24-Port Cat6 Patch Panel 568B | 1 |
| N252-048 | 48-Port Cat6 Patch Panel 568B | 1 |
| SRBOLTDOWN | Bolt-Down Kit (Secures included stabilizing brackets or optional stabilizing plates to facility floor.) | 1 |
| SRCABLEDUCTVRT | 6-ft. (1.8 m) Vertical Cable Manager (Double finger duct with cover; toolless mounting.) | 1 |
| SRCABLEVRT3 | 3" Wide High Capacity Vertical Cable Manager (Double finger duct; toolless mounting.) | 1 |
| SRCABLEVRT6 | 6" Wide High Capacity Vertical Cable Manager (Double finger duct with cover; toolless mounting.) | 1 |
| SRCABLEVRT12 | 12" Width High Capacity Vertical Cable Manager (Double finger duct with cover; toolless mounting.) | 1 |
| SRCABLEDUCT1U | 1U Horizontal Cable Manager (Finger duct with cover.) | 1 |
| SRCABLELADDER | 10-ft. x 1-ft. (3 m x 0.3 m) Cable Ladder (Includes 2 sections; requires SRCABLETRAY.) | 1 |
| SRCABLERINGVRT | 6-ft. (1.8 m) Vertical Cable Manager (Flexible ring type; toolless mounting.) | 1 |
| SRCABLERING1U | 1U Horizontal Cable Manager (Flexible ring type.) | 1 |
| SRCABLERING2U | 2U Horizontal Cable Manager (Flexible ring type.) | 1 |
| SRCAGENUTS | Square Hole Hardware Kit (Includes 50 M6 screws and washers.) | 1 |
| SRCASTER | Heavy-Duty Rolling Caster Kit (Includes 4 casters. Casters are included with 48/42/25U enclosures.) | 1 |
| SRSHELF2P | 2U Cantilever Fixed Shelf (60 lb / 27 kg capacity; 18-in. / 457 mm depth.) | 1 |
| SRSHELF4PHD | Heavy-Duty Fixed Shelf (250 lb / 113 kg capacity; 26 in / 660 mm depth.) | 1 |
| SRSHELF4PKYBD | Keyboard Shelf (25 lb / 11 kg capacity; 16-in. / 406 mm depth.) | 1 |
| SRSHELF4PSL | Standard Sliding Shelf (50 lb / 22 kg capacity; 26 in/ 660 mm depth.) | 1 |
| SRSHELF4PSLHD | Heavy-Duty Sliding Shelf (100 lb / 45 kg capacity; 26 in / 660 mm depth.) | 1 |
| SRFAN3U | 3U Fan Panel, 120V (3 high-performance fans; 210 CFM; 5-15P plug.) | 1 |
| SRXFAN3U | 3U Fan Panel, 230V (3 high-performance fans; 210 CFM; C14 inlet.) | 1 |
| SR1UPANEL10 | 1U Blanking Panel Kit (10 pieces; toolless mounting.) | 1 |
| SR1UPANEL50 | 1U Blanking Panel Kit (50 pieces; toolless mounting.) | 1 |
| UPSHDEARKIT | Heavy-Duty Mounting Ear Kit (Supports 2U cabinets up to 65 lb / 29 kg from front vertical rails in 4-post or 2-post racks and enclosures.) | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=3209.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.