



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SR4POST25

25U 4-Post SmartRack Open Frame Rack - Organize and Secure Network Rack Equipment



Highlights

- 25U 4-post open frame rack
- Black steel with square, numbered mounting holes
- Toolless button holes to accept PDUs or cable managers

Description

SmartRack 4-post open frame racks are ideal for cost conscious 19 inch rack mount applications. Multiple units can be bolted together side by side.

Package Includes

- SR4POST25
- Installation hardware
- 32x pieces of M6 cage nuts, screws, and washers for equipment mounting
- Cable management hooks
- Owner's manual with warranty information

Features

- Supports 1000lbs of rackmount equipment
- Adjustable mounting depth (22 to 39 inches)
- Textured powder coat finish
- Heavy-duty cold-rolled steel construction
- Numbered mounting positions
- Bolt down provisions
- Self squaring design
- Black finish
- Easy assembly

Specifications

PHYSICAL	
Installed whole system maximum rack depth (inches)	39.3
Installed whole system maximum rack depth (cm)	99.82

Installed whole system minimum rack depth (inches)	22
Installed whole system total rack space height (rack spaces)	25U
Shipping weight (lbs)	46
Shipping weight (kg)	20.7
Unit Dimensions (HWD/cm)	125.2 x 51.3 x 55.9~99.8 (depth adjustable)
Shipping Dimensions (HWD/in)	4.13 x 5.71 x 56.5
Shipping Dimensions (HWD/cm)	10.5 x 14.5 x 143.51
Unit weight (lbs)	45
Unit weight (kg)	20.25
Unit Dimensions (cm)	125.2 x 51.31 x 55.88~99.1 (depth adjustable)
Unit Dimensions (in)	49.3 x 20.2 x 22~39.3 (depth adjustable)
Color	Black
Weight Capacity - Stationary (lbs)	1000
Installed whole system minimum rack depth (cm)	55.88
Weight Capacity - Stationary (kg)	453.6
SPECIAL FEATURES	
Grounding lug	Included screws, nuts, and washers secure user-supplied grounding wire to Front or Back frames
CERTIFICATIONS	
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	EIA-310-D, IEC 60297-3-100, DIN 41494, RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
SRFAN3U	3U Fan Panel, 120V (3 high-performance fans; 210 CFM; 5-15P plug.)	1
SRXFAN3U	3U Fan Panel, 230V (3 high-performance fans; 210 CFM; C14 inlet.)	1
SR1UBRUSH	1U Cable Pass-Through Panel with Brush Strip	1
SR1UPANEL10	1U Blanking Panel Kit (10 pieces; toolless mounting.)	1
SRCABLEDUCT1U	1U Horizontal Cable Manager (Finger duct with cover.)	1
SRCABLERING1U	1U Horizontal Cable Manager (Flexible ring type.)	1

SRCABLERING2U	2U Horizontal Cable Manager (Flexible ring type.)	1
SRSHELF4PHD	Heavy-Duty Fixed Shelf (250 lb / 113 kg capacity; 26 in / 660 mm depth.)	1
SRSHELF4PKYBD	Keyboard Shelf (25 lb / 11 kg capacity; 16-in. / 406 mm depth.)	1
SRBOLTDOWN	Bolt-Down Kit (Secures included stabilizing brackets or optional stabilizing plates to facility floor.)	1
SRCAGENUTS	Square Hole Hardware Kit (Includes 50 M6 screws and washers.)	1
SRCASTER	Heavy-Duty Rolling Caster Kit (Includes 4 casters)	1
UPSHDEARKIT	Heavy-Duty Mounting Ear Kit - Supports 2U cabinets up to 65 lb / 29 kg from front vertical rails in 4-post or 2-post racks and enclosures.)	1
N252-012	12-Port Cat6 Patch Panel 568B, 1U	1
N252-024	24-Port Cat6 Patch Panel 568B, 1U	1
N252-048	48-Port Cat6 Patch Panel 568B	1
B040-008-19	NetController 19" VGA Console KVM Switch - 8 Port	1
B020-U08-19-IP	Console KVM Switch - 8-Port NetDirector 1U Rackmount Console IP KVM Switch w/19" LCD	1
B020-U08-19-K	Console KVM Switch - 8-Port NetDirector 1U Rackmount Console KVM Switch w/19" LCD + 8 PS2/USB Combo Cables	1
B040-016-19	NetController 19" VGA Console KVM Switch - 16 Port	1
B021-000-17	Rackmount Console - 1U Rackmount Console with 17" LCD	1
B021-000-19	Rackmount Console - 1U Rackmount Console with 19" LCD	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.triplite.com/en/products/model.cfm?variables.txtModelID=4794.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.