

FREEDM® One Tight-Buffered, Interlocking Armored Cable, Plenum

12 F, 62.5 µm multimode (OM1)

CORNING

Corning Cable Systems FREEDM® One Interlocking Armored Cables are flame-retardant, indoor/outdoor, cables designed for interbuilding and intrabuilding back-bone installations that eliminate the need for a transition splice when entering the building. Encased in a spirally wrapped, aluminum interlocking armor for ruggedness and superior crush resistance, these cables are ideal for industrial and heavy traffic areas and installations requiring extra protection for optical cables. These cables are protected against water penetration by innovative water-blocking technology, making it ideal for OSP applications. The flexible, interlocking armored design offers over seven times the crush protection compared to unarmored cables (as characterized to ICEA-696) and allows easy one step installation, thereby reducing the overall installation costs. The UV-resistant, flame-retardant jacket is rugged, durable and easy to strip.

Features and Benefits

Waterblocking technology
OSP (outdoor) applications



Flexible, interlocking armor design
Seven times crush protection compared to unarmored cables

UV-resistant, flame-retardant jacket
Rugged, durable and easy to strip

Standards

Approval and Listings National Electrical Code® (NEC®) OFCP, CSA FT-4, ICEA S-104-696

Flame Resistance NFPA 262 (for plenum, riser and general building applications)



CORNING

FREEDM® One Tight-Buffered, Interlocking Armored Cable, Plenum

12 F, 62.5 µm multimode (OM1)

CORNING

Specifications

General Specifications

Environment	Indoor/Outdoor Cables
Application	Aerial, Direct Buried, Duct, General Purpose Horizontal, Vertical Riser, Plenum
Cable Type	Tight-Buffered
Product Type	Interlocking armor
Flame Rating	Plenum (OFCP)
Fiber Category	62.5 µm MM (OM1)

Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-10 °C to 60 °C (14 °F to 140 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design

Central Element	Dielectric
Fiber Count	12
Tight Buffer Color	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Tensile Strength Elements / Armoring - Layer 1	Water-swellable strength members
Inner Jacket Material	Flame-Retardant, UV-Resistant
Tensile Strength Elements / Armoring - Layer 2	Interlocking armor
Number of Ripcords	2
Outer Jacket Material	Flame-Retardant, UV-Resistant
Outer Jacket Color	Black

Mechanical Characteristics Cable

Nominal Inner Cable Diameter	6.3 mm (0.25 in)
Nominal Outer Diameter	12.5 mm (.49 in)
Weight	140 kg/km (94 lb/1000 ft)
Min. Bend Radius Installation	95 mm (3.7 in)

CORNING

FREEDM® One Tight-Buffered, Interlocking Armored Cable, Plenum

12 F, 62.5 µm multimode (OM1)

CORNING

Mechanical Characteristics Cable

Min. Bend Radius Operation	63 mm (2.5 in)
Max. Tensile Strengths, Short-Term	675 N (150 lbf)
Max. Tensile Strengths, Long-Term	200 N (45 lbf)

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Core Diameter	62.5 µm
Fiber Type	Multimode
Fiber Category	OM1
Fiber Code	K
Performance Option Code	30
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	3.4 dB/km / 1 dB/km
Min. Overfilled Launch (OFL) Bandwidth	200 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	220 MHz*km / -
Serial 1 Gigabit Ethernet	300 m / 550 m
Serial 10 Gigabit Ethernet	33 m / -

Notes: 1) Improved attenuation and bandwidth options available
2) Bend-insensitive single-mode fibers available on request
3) Contact a Corning Cable Systems Customer Service Representative for additional information

Ordering Information

Order Number	012K8P-30130-A3
Product Description	FREEDM® One Tight-Buffered, Interlocking Armored Cable, Plenum, 12 F, 62.5 µm multimode (OM1)

Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.
Corning Cable Systems is ISO 9001 certified. © 2011 Corning Cable Systems. All rights reserved.

CORNING