### **Fiber Zone Box**

4 rack units, holds 12 CCH panels or modules



Corning Cable Systems Fiber Zone Box is a cabling infrastructure distribution facility for passive applications in zone cabling. It is ideal for interconnect or cross-connect points in data center zone or horizontal distribution areas. Sized to fit a 2 x 2 ft drop ceiling or subfloor opening, it can also be mounted to a wall and is equipped with a sealing to inhibit dust and liquid penetration.

The box accepts up to 12 LANscape® Solutions CCH connector panels or modules for LC duplex, SC, SC duplex, FC, MT-RJ, ST® Compatible and MTP® Connector fiber termination and distribution. It will also accept up to 24 buffer tube fan-out kits. Each of the 12 cable entry points contain 1-in and 2.5-in concentric knockouts. The multiposition bulkhead provides four rack units of 19-in rack-mountable space. The white, hinged removable door matches ceiling tiles and is equipped with a key lock.



### **Features and Benefits**

#### Removable backplate

Eases installation

#### Robust lock

Additional security

UL-Listed to United States and Canadian standards, NEMA 1, 2, 5, 12K rated

Safety

#### Includes 4U of 19-in rack space

Copper and fiber options

#### Multiposition bulkhead

Dramatically increases ease of use in subfloor/overhead applications

#### **Standards**

#### **Approval and Listings**

UL-Listed to the United States and Canadian safety standards, NEMA, 1, 2, 5, 12K rated

# **Fiber Zone Box**

4 rack units, holds 12 CCH panels or modules



# **Specifications**

General Specifications	
Application	Enterprise Networks, Data Center
Mounting Type	Wall-Mountable, Ceiling mount, Floor mount
Product Type	Wall-Mountable Hardware

Design - Hardware	
Housing Type	FZB
Housing Color	White
Maximum Number of Panels per Housing	12
Panel or Module Type	CCH
Splice Tray Options	Accommodates up to (12) 0.2 in or (6) 0.4 in category S, or category R splice trays

Mechanical Characteristics	
Dimensions (HxWxD)	54 cm x 54 cm x 21.6 cm (21.25 in x 21.25 in x 8.5 in)

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/ EG

## **Ordering Information**

Part Number FZB-0	04U
Product Description Fiber ules	Zone Box, 4 rack units, holds 12 CCH panels or mod-



### **Fiber Zone Box**

4 rack units, holds 12 CCH panels or modules



## **Shipping Information**

Units per Delivery	1/1
Package Contents	Housing; installation guide; label, unit ID; label, port identification for 12 panels; 12 blank panels; 12 tie wraps, 1/8 x 4, white; edge grommet, nylon, 12-in; 32 screws, #6-32 x 0.25-in; 2 Universal Cable Clamp (UCC) Kits with 5 cable inserts; 2 brackets for mounting UCC clamp; 2 fan-out brackets; 4 wall-/floor-mounting brackets; 2 trim plates, floor, FZB-04U; 6 6-32 x .25 Phillips; ground bar EM4250-3550; 2 screws, #8-32 and 2 lock washers, #8
Shipping Weight	6.8 kg (15 lb)



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

