


### SRK



#### **Product Description**

Silicone-rubber insulation Braided K-Fiber jacket 600 V UL AWM Style 3410

#### **Applications**

For installation above grade or in conduit in applications where high-temperature resistance to flame with circuit integrity is required. Suited for internal wiring of appliances and electrical equipment where moisture, cold and/or heat may be present.

## **Specifications**

- CONDUCTOR: Tinned, annealed copper per ASTM B-33, Class H stranded per ASTM B-173
- INSULATION: Silicone rubber
- OVERALL JACKET: K-Fiber braid with abrasion-resistant finish
- STANDARDS: Meets the UL requirements for AWM Style 3410 (26-500 kcmil), meets the UL requirements for Type SA-90°C (14-500 kcmil), sizes 1/0 and larger pass the IEEE 383 Flame Test
- AMPACITY: Based on three single insulated 200°C rated conductors in raceway or cable with an ambient temperature of 40°C per 2008 NEC 310.18
- TEMPERATURE: 150°C 200°C
- VOLTAGE: 600 V

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

Anixter is a leading global supplier of communications and security products, electrical and electronic wire and cable, fasteners and other small components. We help our customers specify solutions and make informed purchasing decisions around technology, applications and relevant standards. Throughout the world, we provide innovative supply chain management solutions to reduce our customers' total cost of production and implementation.

# Product Data Sheet | Anixter Catalog Page



Diameters and weights may vary among manufacturers.

Part No.	Conductor Size AWG	No. of Strands	Insulation Thickness (in.)	Braid Thickness (in.)	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.	Amps per Conductor
8MK-0801	8	133	0.060	0.035	0.368	96	83
8MK-0601	6	133	0.060	0.035	0.413	134	110
8MK-0401	4	133	0.060	0.035	0.469	192	125
8MK-0201	2	133	0.060	0.035	0.538	281	171
8MK-0101	1	259	0.080	0.035	0.621	366	197
8MK-1011	1/0	259	0.080	0.035	0.670	447	229
8MK-2021	2/0	259	0.080	0.035	0.723	546	260
8MK-4041	4/0	259	0.080	0.036	0.847	819	346
8MK-2501	250	427	0.095	0.035	0.931	981	385
8MK-3501	350	427	0.095	0.035	1.050	1,332	486
8MK-5001	500	427	0.095	0.035	1.201	1,837	593

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com