Product Data Sheet | Anixter Catalog Page



Type G-GC CV Cured



Product Description

EPR insulation Thermoset jacket 90°C, 2 kV

Applications

For use as flexible power lead with portable or mobile equipment such as pumps, welders, mining machines and mine conveyor equipment.

Specifications

- CONDUCTOR*: Rope-stranded, uncoated copper per ASTM B-172
- INSULATION: Ethylene Propylene Rubber (EPR)
- COLOR CODE: Black, white and red
- GROUND AND GROUND CHECK: Insulated, stranded copper
- ASSEMBLY: Three insulated conductors, two ground conductors and one yellow ground check conductor, cabled with fillers
- OVERALL JACKET: CV cured thermoset compound
- STANDARDS: Meets the requirements of ICEA S-75-381 (NEMA WC58), accepted by MSHA and marked with the manufacturer's P number, UL Listed Type G-GC per UL Subject 1650 requirements
- AMPACITY: Based on an ambient temperature of 40°C and conductor temperature of 90°C per ICEA S-75-381 table. Additional ampacities available in 2008 NEC Table 400.5(B)
- TEMPERATURE: -40°C to 90°C
- VOLTAGE: 2 kV

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

Anixter is a leading global supplier of communications and security products, electrical and electronic wire and cable, fasteners and other small components. We help our customers specify solutions and make informed purchasing decisions around technology, applications and relevant standards. Throughout the world, we provide innovative supply chain management solutions to reduce our customers' total cost of production and implementation.

Product Data Sheet | Anixter Catalog Page



Lead cured available upon request (5F-XXXX). Diameters, ground check size and weights may vary among manufacturers.

Part No.	Conductor Size AWG/kcmil	No. of Strands	No. of Conductors	Insulation Thickness (in.)	Ground Wire Size Number	Ground Wire Size AWG	Ground Check Size AWG	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.	Amps per Conductor
5F-0803C	8	133	3	0.060	2	10	10	0.970	682	59
5F-0603C	6	133	3	0.060	2	10	10	1.050	830	79
5F-0403C	4	133	3	0.060	2	8	10	1.190	1,128	104
5F-0203C	2	133	3	0.060	2	7	10	1.330	1,451	138
5F-0103C	1	133	3	0.080	2	6	8	1.490	1,856	161
5F-1013C	1/0	259	3	0.080	2	5	8	1.620	2,270	186
5F-2023C	2/0	259	3	0.080	2	4	8	1.750	3,020	215
5F-3033C	3/0	259	3	0.080	2	3	8	1.860	3,660	249
5F-4043C	4/0	259	3	0.080	2	2	8	1.970	4,147	287
5F-2503C	250	427	3	0.095	2	2	8	2.390	6,060	320
5F-3503C	350	427	3	0.095	2	1/0	8	2.680	7,058	394
5F-5003C	500	427	3	0.095	2	2/0	8	3.030	8,900	487

Conductor color code chart

Number of Conductors	Cable Types	Color Identification	Number of Conductors	Cable Types	Color Identification
2	All	Black, White	4	G Round	Black, White, Red, Orange
3	G or G-GC Round or Flat	Black, White, Red	4	W Round	Black, White, Red, Green
3	SHD-GC	Black, White, Red	5	W Round	Black, White, Red, Green, Orange
3	W Round and Flat	Flat Black, White, Green	Ground Check Conductor	SHD-GC, GGC and MPF-GC	Yellow

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com