

**B&B ELECTRONICS**

Modular Protocol-Independent, Fiber Mode Converter via SFP Modules

IE-iMcV-ModeConverter



PRODUCT FEATURES

- Interchangeable SFP modules allow for multiple fiber mode/type conversion options (single-mode, multi-mode, single-strand, long haul, short haul, etc.)
- Extended operating temperatures
- DDMI enabled SFPs support SNMP when installed in a compatible managed chassis
- Modular, hot-swappable architecture reduces operational costs associated with product installation, upgrades and maintenance
- Ideal for use with B&B Electronics' SFPs
- Supports a full range of SFP modules offering various transmission speeds, from 10 Mbps up to 2.4 Gbps*

The IE-iMcV-ModeConverter is an SNMP manageable module that allows network operators to incorporate multiple fiber types and wavelengths within a network. It installs in the modular, SNMP-manageable iMediaChassis series and in the unmanaged MediaChassis series.

The IE-iMcV-ModeConverters are protocol-independent with dual SFP ports which can provide a single conversion between different wavelengths or single-mode and multimode fiber, single-mode to single-mode fiber or multimode to single-strand single-mode fiber. The IE-iMcV-ModeConverter modules support a variety of user configurable features such as LinkLoss forcing a gigabit SFP to 100Mbps. Additionally, since the IE-iMcV-ModeConverter is an Industrial Equipment (IE) device, the unit operates in environments that demand extended operating temperatures.

The IE-iMcV-ModeConverter uses MSA Compliant SFP modules to provide greater fiber flexibility in the network environment. The hot-swappable nature of SFPs and the numerous fiber modes and types that are available allow for easy configuration and future upgrading as network demands evolve.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION	FIBER PORTS	DISTANCE
IE-ModeConverter SFP/SFP with AC Adapter **			
850-19500	SFP	2	Various

* Certified at 1.25 Gbps, 2.4 Gbps is achievable

** SFP fibers sold separately



iView: Windows 2000/XP/Vista/Win7



IN THE FIELD

High Bandwidth for Dubai Mall

Industry: Enterprise IT

Product: IE-Mode Converters w/ SFP modules;
IE-PowerTray/18 High-density Chassis



[www.bb-elec.com/
DubaiMall](http://www.bb-elec.com/DubaiMall)

Carrier data charges
may apply.

Modular Protocol-Independent, Fiber Mode Converter via SFP Modules

IE-iMcV-ModeConverter



SPECIFICATIONS

TECHNICAL

Includes two SFP ports
Protocol-independent operation
Converts between dissimilar fiber modes and wavelengths
Includes diagnostic LEDs
Hot-swappable architecture
Modular Form Factor

Extended temperature range from -40° to +85° C
Compatible with IMC Networks' SFPs and all
standard MSA compliant SFP devices

STANDARD COMPLIANCE

SFP-MSA SFP standard (September 14, 2000)
SFF-8472 DDM1 standard (Revision 1.0)

MECHANICAL

Dimensions 4.19" x 0.78" x 2.75"
(10.6 cm x 1.98 cm x 6.99 cm)
Shipping Weight 0.25 lbs (0.11 kg)

POWER

422mA with SFP ports populated (Typical @ 5V)

ENVIRONMENTAL

Operating Temperature: -40° to +185° F (-40° to +85° C)
Storage Temperature: -40° to +185° F (-40° to +85° C)
Operating Humidity 5% to 95% (non-condensing),
0 – 10,000 ft. altitude

REGULATORY APPROVALS

FCC Class A
UL/cUL, CE

MECHANICAL DIAGRAM

(dimensions in inches)

