



F137CED2
FlexTwist™ Flexible Twist for WR137, 5.725–6.425 GHz, with interface types CPR137G and CMR137, 600 mm

Electrical Specifications

Operating Frequency Band	5.725 – 6.425 GHz
Attenuation	0.09 db/ft 0.30 db/m
Average Power	2000 W
Peak Power	500.0 kW
VSWR	1.03


General Specifications

Component	Flexible Twist
Waveguide Size	WR137 WG14 R70
Interface	CPR137G
Interface 2	CMR137
Length	600 mm 24 in


Mechanical Specifications

Maximum Twist	214.00 °/m 65.00 °/ft
Minimum Bend Radius, Multiple Bends (E Plane)	102.00 mm 4.00 in
Minimum Bend Radius, Multiple Bends (H Plane)	204.00 mm 8.00 in
Pressurization, maximum	30 psi 205 kPa


Component



Interface



Interface 2



Regulatory Compliance/Certifications

Agency RoHS 2011/65/EU China RoHS SJ/T 11364-2006 ISO 9001:2008	Classification Compliant by Exemption Above Maximum Concentration Value (MCV) Designed, manufactured and/or distributed under this quality management system
---	--

Product Specifications

COMMScope®

F137CED2

POWERED BY

