



SD-003-KIT3

Static Desiccator Dehydrator, with remote mounting accessories kit

- To meet our global customer's RoHS environmental needs, we have changed our desiccant to a cobalt-chloride free desiccant. Orange color when dry, turns green when saturated.

Dimensions

| | |
|------------------------|-------------------|
| Net Weight | 0.2 kg 0.4 lb |
| Product Depth | 50.8 mm 2.0 in |
| Product Height | 127.0 mm 5.0 in |
| Product Width | 50.8 mm 2.0 in |
| Gross Weight, Packed | 0.2 kg 0.4 lb |
| Product Depth, Packed | 127.0 mm 5.0 in |
| Product Height, Packed | 50.8 mm 2.0 in |
| Product Width, Packed | 50.8 cm 20.0 in |

Electrical Specifications

| | |
|-----------------------|--------------------------------------|
| Operating Temperature | -29 °C to +49 °C (-20 °F to +120 °F) |
|-----------------------|--------------------------------------|

General Specifications

| | |
|--------------------------|---|
| Dehydrator Type | Desiccant |
| Volume Capacity, minimum | 0.0 L 0.0 ft ³ |
| Volume Capacity, maximum | 28.3 L 1.0 ft ³ |
| Desiccant Capacity | 283 liters (10 cu ft) at 80% RH, +20 °C |
| Includes | 1/4 in vinyl tubing 90° elbow fitting Instruction sheet Polyethylene splice union fitting Static desiccator |
| Mount Type | Pole |
| Port Count | 1 |
| Port Type | 3/8 in PE tube x 1/8 NPT |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |