

**42396A-1****Butterfly Hanger for 1-1/4 in coaxial cable and elliptical waveguide 64**

## Dimensions

Nominal Size	1-1/4 in
Compatible Diameter, maximum	43.180 mm   1.700 in
Compatible Diameter, minimum	37.592 mm   1.480 in
Height	59.00 mm   2.32 in
Length	76.20 mm   3.00 in
Width	38.10 mm   1.50 in

## Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

## General Specifications

Hanger Type	Standard butterfly hanger
Cables per Hanger	1
Color	Silver
Material Type	Stainless steel
Ordering Note	CommScope® standard product in the United States and Canada
Package Quantity	10

## Mechanical Specifications

Axial Load Capability, minimum with no cable slippage	=5 times cable weight
Corrosion Resistance, minimum with no degradation	=500 hours in salt spray chamber
Mounting	3/8 in (M10) drilled cable ladder
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Vibration Survival	=4 hours at resonant frequency

## Packed Dimensions

Height	26.0 cm   10.2 in
Length	9.0 cm   3.5 in
Shipping Weight	0.53 kg   1.16 lb
Width	9.0 cm   3.5 in

## Regulatory Compliance/Certifications

Agency	Classification
--------	----------------

# Product Specifications

COMMScope®

42396A-1

POWERED BY



RoHS 2011/65/EU

China RoHS SJ/T 11364-2006

ISO 9001:2008

Compliant

Below Maximum Concentration Value (MCV)

Designed, manufactured and/or distributed under this quality management system

