

Anixter Level 2 for Industrial Network Environments

Industrial Ethernet Tray Cable: Cat 5e 22-4 Pair Solid UTP PLTC



L2-5E-SOL-UTP-TC-02

4 Pair 22 AWG PLTC, UTP solid bare copper conductors, polyolefin insulation, industrial grade sunlight- and oil-resistant PVC jacket, rip cord. Sequential marking at 2 foot intervals.

Physical Characteristics (Overall)			
Conductor			
# Pairs	4		
AWG	22		
Stranding	Solid		
Material	BC - Bare Copper		
Diameter	0.026 in.		
Total # of Conductors	8		
Insulation			
Material	PO - Polyolefin		
Wall Thickness	0.011 in.		
Diameter	0.048 in.		
Outer Shield			
Туре	Unshielded		
Outer Jacket			
Material	Industrial Grade PVC - Polyvinyl Chloride		
Outer Jacket Ripcord	Yes		



	Overall Cable			
Overall Nominal Diameter	0.301 in.			
Pair Color Code Chart				
1	White/Blue & Blue			
2	White/Orange & Orange			
3	White/Green and Green			
4	White/Brown and Brown			
Med	chanical Characteristics (Overall)			
Installation Temperature Range	-25°C To +75°C			
Operating Temperature Range	-40°C To +75°C			
Bulk Cable Weight	138 lbs.			
Max. Recommended Pulling Tension	40 lbs.			
Min. Bend Radius/Minor Axis	0.3 in.			
Applicable Spec	cifications and Agency Compliance (Overall)			
Applicable	Standards & Environmental Programs			
CEC/C(UL) Specification	CMR			
NEC/(UL) Specification	CMR, CMX-Outdoor, PLTC			
EU Directive 2011/65/EU (ROHS II)	Yes			
EU Directive 2000/53/EC (ELV)	Yes			
EU Directive 2002/95/EC (RoHS)	Yes			
EU RoHS Compliance Date (mm/dd/yyyy)	1/1/2004			
EU Directive 2002/96/EC (WEEE)	Yes			
EU Directive 2003/11/EC (BFR)	Yes			
CA Prop 65 (CJ for Wire & Cable)	Yes			
MII Order #39 (China RoHS)	Yes			
Other Specification	NEMA WC-63.1 Category 5e			
Telecommunication Standards	Category 5e - TIA 568.C.2			
Flame Test				
UL Flame Test	UL1666 Vertical Riser			
CSA Flame Test	FT4			
IEEE Flame Test	1202			



Suitability			
Suitability – Indoor	Yes		
Suitability - Outdoor	Yes		
Sunlight Resistance	Yes		
Oil Resistance	Yes		
Plenum/Non-Plenum			
Plenum (Y/N)	No		

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • OEM Supply – Fasteners Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

Anixter is a leading global distributor of enterprise cabling and security solutions, electrical and electronic wire and cable, and OEM supply – fasteners and other small parts.

We reduce risk, complexity and cost from our customers' purchasing decisions, business processes and supply chains.