

Internal SAS Cable, 4-in-1 32Pin (SFF-8484) to 4 x 7pin Cable, 1M (3-ft.)

MODEL NUMBER: **S502-01M**



Description

Tripp Lite's 32-pin SFF-8484 to 4 x 7-pin internal SAS cable (Serial Attached SCSI) cable is ideal for connecting SAS controllers to individual SAS/SATA disk drives. High-performance cable provides differential pair signaling with less than 5ps/m in pair skew, improved EMI protection, and 3.0Gbs data rate with rates up to 6.0Gbs.

Thinner, flexible cable enables more efficient routing, with improved airflow and thermal mechanics. Configuration of storage devices is simplified. Tripp Lite SAS assemblies are RoHS compliant and feature a

Features

- SFF-8484 to 4 x 7pin SAS Cable - 1 meter
- Supports data rates up to 6.0Gbs
- Thin, flexible cable for easy routing and increased airflow
- RoHS Compliant

Specifications

OVERVIEW	
Style	SCSI
Model Type	Internal
Cable Types	SAS
INPUT	
Cable Length (ft.)	3
Cable Length (m)	1

Highlights

- 32-pin SFF-8484 to 4 x 7-pin internal SAS cable
- Supports data rates of up to 6.0Gbs
- Straight backshell configuration
- 1 meter in length

Applications

- SAS Host Bus Adapters (HBA) such as LSI Logic SAS3442X-R and SAS3442E-R, utilizing internal SFF-8484 mating connectors

System Requirements

- SAS Host Bus Adapter and Backplane with SFF-8484 mating connector

Package Includes

- 1-Meter Internal SAS 4-in-1 SFF-8484 to 4 x 7pin Cable



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

PHYSICAL	
Color	Red
CONNECTIONS	
Connector A	SFF-8484
Connector B	7 PIN SATA (MALE)
Number of Connectors	5
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.