



Building Entrance Terminals

INDOOR - 710 CONNECTOR SERIES - BET



1880ENS1-25

25 PAIR - INDOOR BET - 710/110 - SPLICE CHAMBER - NO COVER

Product Specifications

UL497 Primary Protector for Communication Circuits

NAFTA Country of Origin: CANADA - All Models are "Buy America Act" Approved.

These 16 AWG steel building entrance terminals feature a 710 style connector for use in specialized OSP installations including military, healthcare and educational applications. Also included are multiple external and internal ground lugs as well as a splice chamber. UL Approval standard on all terminals. Standard 5-pin protector modules, available in gas tube and solid state versions, are sold separately. Call for more detailed information on RDUP/RUS-listed units.

Features & Benefits

- 16 AWG Powder Coated Steel Construction
- Equipped with an Internal 26 AWG Fuse Link
- External Ground Connectors Accept 6 - 14 AWG Wire
- Industry Standard 5 Pin Design
- Exceeds UL497 Primary Protection Standards
- Stackable with Connection Grommets Included
- Input/output Connectors Accept 22 - 26 AWG Wire



1880ENS1-25

Ordering Information

Model Number	Stock Code	Pair Count	Input	Output	Dimensions (H" x W" x D")	Weight (lbs)
1880ENS1-25	305307	25	710	110	8.75 x 12.75 x 4.75	7.5



Building Entrance Terminals

INDOOR - 710 CONNECTOR SERIES - BET




1880ENS1-25

25 PAIR - INDOOR BET - 710/110 - SPLICE CHAMBER - NO COVER

Physical Dimensions

UL497 Primary Protector for Communication Circuits

8.75 x 12.75 x 4.75
(H" x W" x D")



Notes

Installation:

Indoor Wall Mount

710 Connector Input - 3.5' 24 AWG Cable Stub

Previous Model Number : 1880ENS1-25G

Splice Chamber: Separate enclosure and cover for OPS gel filled Input cable

RUS Approved Material - 2011 Edition RUS Publication 344-2 (Section 4.1.2 and 4.2)

Circa Telecom, Inc © 2013 - Version 1.03