

## **Enclosed T&B Catalog Number:**

T400LB4-48/XD

**UPC Number:** 80432519917 **Status:** Active

**Description:** 

Enclosed, extreme duty PST softstarter rated for 400 horsepower at 480V  $^{\Delta C}$ 

AC.	
Features	
	PST extreme duty provides reliable reduced voltage
	starting, and is our most advanced softstarter
	Short circuit protection
	Emergency start bypass
	Redundant electronic overload
	Built and tested to provide 500% rated current for
	30 seconds
	UL508A label, UL service entrance rating
	A door mounted ABB hand-off-auto switch
	Three vibration resistent, LED type pilot lights
	Door interlocked disconnect handle that is padlock-
	able and defeatable
Standards	
	UL508A, NEMA 4X
Application	
	Extreme duty designed for high inertia load applica-
	tions, such as rock crushers, mixers, hammer mills,
	and chippers
	By using closed loop current control in addition to
	voltage ramping the PST helps get every bit of per-
General	formance from weak power systems
General	
Series	PST
Dimension Information	
H x W x D (inches)	60 x 36 x 16
Specifications	
Voltage	480V AC
Packaging	
T&B Inner Pack	1
Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	700 lbs. Each
	: 53 1001 = 5511

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com