


## 1816P Multi-Conductor - CMP Rated Cable



For more Information  
please call

1-800-Belden1

**General Description:**

22 AWG stranded (7x30) TC conductor, polyolefin insulation, individually shielded with bonded Beldfoil®, numbered/color-coded Solef jackets, jackets and shields are bonded so both strip simultaneously, overall fluorocopolymer jacket and nylon rip cord.

**Usage (Overall)**

Suitable Applications: Outdoor Applications, Sports Stadium

**Physical Characteristics (Overall)****Conductor**

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
6	22	7x30	TC - Tinned Copper	0.030

Total Number of Conductors: 12

**Insulation**

Insulation Material:

Insulation Material
FEP

**Inner Shield**

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
22

Inner Shield Drain Wire Stranding: 7x30

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

**Inner Jacket**

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVDF	0.119

**Outer Jacket**

Outer Jacket Material:

Outer Jacket Material
PVDF

Outer Jacket Ripcord: Yes

**Overall Cable**

Overall Cabling Color Code Chart:

Number	Color
1	Gray #1
2	Gray #2
3	Gray #3
4	Gray #4
5	Gray #5
6	Gray #6

Overall Nominal Diameter: 0.387 in.

**Pair**

Pair Color Code Chart:

Color
Red & Black

## 1816P Multi-Conductor - CMP Rated Cable

**Mechanical Characteristics (Overall)**

Operating Temperature Range:	-40°C To +150°C
Bulk Cable Weight:	63 lbs/1000 ft.
Max. Recommended Pulling Tension:	188 lbs.
Min. Bend Radius/Minor Axis:	4 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	12/01/2011
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

**Flame Test**

UL Flame Test:	UL910 Plenum
CSA Flame Test:	FT6

**Suitability**

Suitability - Indoor:	Yes
-----------------------	-----

**Plenum/Non-Plenum**

Plenum (Y/N):	Yes
Non-Plenum Number:	1816R

**Electrical Characteristics (Overall)****Nom. Capacitance Conductor to Conductor:**

Capacitance (pF/ft)
31

**Nom. Capacitance Cond. to Other Conductor & Shield:**

Capacitance (pF/ft)
56

**Nominal Velocity of Propagation:**

VP (%)
66

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
14.8

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 10.800 Ohm/1000 ft

**Max. Operating Voltage - UL:**

Voltage
300 V RMS

**Max. Recommended Current:**

Current
1.45 Amps per conductor @ 25°C

**Notes (Overall)**

**Notes:** Pair jackets and shields are bonded so both strip simultaneously with automatic stripping equipment. Beldfoil® provides high reliability with ease of termination.

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1816P 0101000	1,000 FT	84.000 LB	BLACK	C	6 FS PR #22 FEP SLF SLF
1816P 010500	500 FT	42.000 LB	BLACK	C	6 FS PR #22 FEP SLF SLF

## 1816P Multi-Conductor - CMP Rated Cable

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 0    Revision Date: 11-06-2014

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.