



SNA Terminal Blocks

T&B Catalog Number:

035620411

UPC Number:

66201997720

Status:

Active

Description:

Gray, single pole distribution block with 27 mm spacing, 115 Amp rated UL current with screw clamp connection that accepts 2 AWG UL rated wire size

Features

Self-locking clamp design prevents screw loosening

Funneled side entry for up to two ferruled or non-ferruled solid or stranded wires

Touch-safe IP20 protection

High quality steel offers a very high over-torque resistance

Compensates for the flattening of copper under contact pressure

Clamp is protected from harsh environments by a zinc bichromate surface treatment

Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

General

Style	Distribution Block
Color	Gray
Mounting	DIN 3
Series	BRU
Connection Technology	Screw Clamp
UL Wire Range (AWG)	2 max.
Rated IEC Wire Range (Solid) (mm ²)	35
Poles	1

Dimension Information

L x W x H (mm)	75 x 27 x 48
Spacing (mm)	27
L x W x H (in)	2.953 x 1.063 x 1.89
Spacing (inches)	1.063

Specifications

UL Current (Amps)	115
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	2 max.
IEC Voltage (VAC)	600
IEC Current (Amps)	125
CSA Voltage (VAC)	600
CSA Current (Amps)	115

Packaging

T&B Inner Pack	1
Package in Units	25
T&B Sold in UOM	Each

T&B Weight Per UOM

45.5 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com