

**Open**
T&B Catalog Number:

PSR37-600-70

UPC Number:

66201926185

Status:

Active

Description:

Open, compact range PSR softstarter with maximum rated operational current of 34 amps, and 100 to 240V AC control voltage.

Features

Most compact softstarter ABB offers
Flexible mounting: Din Rail or screw mount
Easy set-up of three clearly marked potentiometers
Built in by-pass for energy saving
Run signal relay on all devices
Sophisticated algorithm eliminating the DC-component and thereby providing excellent starting performance
Can be easily connected to ABB manual motor starters via a special designed connection kit
Optional fieldbus communication using Profibus, Modbus, Devicenet, or CANopen

Standards

UL, CSA

Application

Suitable for stopping pumps, designed to reduce water hammering and will allow a superior stop compared to the direct stop resulting from a star delta starter or a DOL starter.

General

Series	PSR
--------	-----

Dimension Information

H x W x D (inches)	7.36 x 2.13 x 6.02
--------------------	--------------------

Specifications

3dmodel	Available on Website
Voltage	208 to 600V AC
Maximum rated operational current (A)	34
Control Voltage	100 to 240V AC

Packaging

T&B Inner Pack	1
Package in Units	12
T&B Sold in UOM	Each
T&B Weight Per UOM	2.4 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com