



SNA Terminal Blocks

T&B Catalog Number:

1SNA400305R1000

UPC Number:

80432551313

Status:

Active

Description:

Gray, feed through terminal block with 22 mm spacing, 159 Amp rated UL current with screw clamp connection that accepts 2 - 0000 AWG UL wire range

Features

Self-locking clamp design prevents screw loosening

Funneled side entry for up to two ferruled or non-ferruled solid or stranded wires

Touch-safe IP20 protection

High quality steel offers a very high over-torque resistance

Compensates for the flattening of copper under contact pressure

Clamp is protected from harsh environments by a zinc bichromate surface treatment

Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

General

| | |
|---|--------------|
| T&B Replacement Catalog Number | 040030510 |
| Style | Feed Through |
| Color | Gray |
| Mounting | DIN 1-3 |
| Series | D 70/22 |
| Connection Technology | Screw Clamp |
| UL Wire Range (AWG) | 2-0000 |
| Rated IEC Wire Range (Solid) (mm ²) | 70 |

Dimension Information

| | |
|------------------|--------------------|
| L x W x H (mm) | 84 x 22 x 74.5 |
| Spacing (mm) | 22 |
| L x W x H (in) | 3.3 x 0.868 x 2.92 |
| Spacing (inches) | 0.866 |

Specifications

| | |
|--------------------|------|
| UL Current (Amps) | 159 |
| UL Voltage (VAC) | 600 |
| IEC Voltage (VAC) | 1000 |
| IEC Current (Amps) | 192 |
| CSA Voltage (VAC) | 600 |
| CSA Current (Amps) | 159 |

Packaging

| | |
|--------------------|------|
| T&B Order Multiple | 10 |
| T&B Inner Pack | 10 |
| Package in Units | 60 |
| T&B Sold in UOM | Each |

T&B Weight Per UOM 0.47 lbs. Each

Certifications

Approvals UL, IEC, CSA

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com