

**Dynamic Braking / DC Drive
T&B Catalog Number:****UPC Number:**

EHDB520C2P-1L

Status:

66201946682

Description:

Active

2 pole, 2 NO, plus 1 NO and 1 NC auxiliary contacts, 520 amp, DC drive, dynamic braking contactor, with a 120V AC coil

Features

Double-break contacts with magnetic arc chutes

Elevator service rated

Standards

cULus

Application

For use with solid state DC adjustable speed drive systems

General

Series	EHDB
Poles	2 NO
Coil Type	AC
Auxiliary Contacts	1 NO and 1 NC

Dimension Information

H x W x D (inches)	10.71 x 7.80 x 8.90
--------------------	---------------------

Specifications

Coil Voltage	120V AC
DC Continuous Current (A)	520
DC Power Pole Make/Break Voltage (V)	600
DC Power Pole Make/Break Current (C)	780
DC Dynamic Braking Pole Make Voltage (V)	600
DC Dynamic Braking Pole Make Current (A)	1040
DC Dynamic Braking Pole Break Voltage (V)	300
DC Dynamic Braking Pole Break Current (A)	680

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	29.23 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com