

**Open Switches**
T&B Catalog Number:

OT40F3/B50

UPC Number:

80432562578

Status:

Active

Description:

3 pole, 40 amps rated at 600 VAC, UL 508, open non-fusible disconnect switch

Features

Quick make, quick brake mechanism

Extremely compact size

Finger-proof construction with no hazardous exposed parts

Application

Industrial control panel disconnects

For use in motor controller and motor overload protection applications

Can be used as an OSHA lockout/tagout disconnect

General

Number of Poles

3

Series

Non-fusible

Approvals

UL Class

UL 508

Dimension Information

H x W x D (inches)

2.13 x 1.38 x 2.20

Specifications

Rated Current (Amps)

40

Rated Voltage AC

600

Packaging

Package in Units

1

T&B Sold in UOM

Each

T&B Weight Per UOM

10.99 lbs. Each

Notes

Bulk pack of 50

For further technical assistance, please contact us...Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.comT&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com