

**Control Relays**
T&B Catalog Number:

NFZ22E-23

UPC Number:

80432555602

Status:

Active

Description:

4 pole, NFZ control relay with control voltage range of 100-250V AC/DC and 4 NO standard auxiliary contacts

Features

NFZ control relays include an electronic coil interface accepting a wide control voltage U_c min. - U_c max. and managing large control voltage variations

Allow direct control by PLC-output # 24 V DC 500 mA and obtain a reduced holding coil consumption

Withstand short dips and voltage interruptions (SEMI F47-0706 compliance)

Built-in surge protection and do not require additional surge suppressors

The control relays have mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1 and include the "Mechanically Linked" symbol on their side

Application

For applications that require small control relays with 4 NO contacts

For pilot duty applications up to 10 amps

General

Series	NF
Poles	4
Coil Type	AC/DC
Auxiliary Contacts	4 NO

Dimension Information

H x W x D (inches)	3.15 x 1.77 x 3.03
--------------------	--------------------

Specifications

3dmodel	Available on Website
Coil Voltage	100-250V AC/DC

Packaging

T&B Inner Pack	1
Package in Units	54
T&B Sold in UOM	Each
T&B Weight Per UOM	69.5 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com