



## SNA Terminal Blocks

### T&B Catalog Number:

1SNA400370R2400

UPC Number:

80432556399

Status:

Active

Description:

Gray, feed through terminal block with 26 mm spacing, 230 Amp rated UL current with screw clamp connection that accepts 2-0000 AWG UL wire range

### Features

Self-locking clamp design prevents screw loosening

Funneled side entry for up to two ferruled or non-ferruled solid or stranded wires

Touch-safe IP20 protection

High quality steel offers a very high over-torque resistance

Compensates for the flattening of copper under contact pressure

Clamp is protected from harsh environments by a zinc bichromate surface treatment

### Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

### General

Style	Feed Through
Color	Gray
Mounting	DIN 1-3
Series	D 95/26
Connection Technology	Screw Clamp
UL Wire Range (AWG)	2-0000
Rated IEC Wire Range (Solid) (mm <sup>2</sup> )	95

### Dimension Information

L x W x H (mm)	87 x 26 x 79.5
Spacing (mm)	26
L x W x H (in)	3.43 x 1.02 x 3.13
Spacing (inches)	1.024

### Specifications

UL Current (Amps)	230
UL Voltage (VAC)	600
IEC Voltage (VAC)	1000
IEC Current (Amps)	232
CSA Voltage (VAC)	600
CSA Current (Amps)	230

### Packaging

T&B Order Multiple	10
T&B Inner Pack	10
Package in Units	30
T&B Sold in UOM	Each
T&B Weight Per UOM	0.48 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)