



## Liquidtight Flexible Cord & Cable Fittings

### T&B Catalog Number:

2708

**UPC Number:**

78621002708

**Status:**

Active

**Description:**

2 in. Black Beauty nylon straight liquidtight cord connector, cord range-1.190 -1.530.

### Features

Hand tightens, no tools needed for assembly.

Segmented chuck provides high mechanical pullout performance, will not cut or damage cord jacket.

### Application

To connect flexible cord to a box or enclosure and provide adequate strain relief.

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & 2; Class III, Div 1 & 2; NEC 501-4(b), 502-4(a)(b), 503-3(a)(b)

Meets Coast Guard CG293

### General

Material	Nylon
----------	-------

### Dimension Information

Hub Size (inches)	2
Dimension A (inches)	5.1
Dimension B (inches)	3.50
Dimension C (inches)	0.84
Cord Range (inches)	1.190-1.530
Throat Diameter (inches)	1.89

### Specifications

3dmodel	Available on Website
Temperature Rating	34 C - 105 C

### Packaging

Package in Units	5
T&B Sold in UOM	Each
T&B Weight Per UOM	0.81 lbs. per 100

### Application Support

T&B Instruction Sheets	ta01320-tb2
Product Overview	Available on Website
Portable Cord Selection Table	Available on Website

### Notes

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & 2; Class III, Div 1 & 2; NEC 501-4(b), 502-4(a)(b), 503-3(a)(b)

### Certifications

RoHS Compliance	Yes
-----------------	-----

## Certifications



File Nbr:  
E 13938

### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:[techsupport@tnb.com](mailto:techsupport@tnb.com)