

#### **RACK-MOUNTABLE FAN PACKAGE**



#### **INDUSTRY STANDARDS**

UL Component Recognized; File No. E61997

EIA RS-310-D CSA certified (blower motor only)

### **APPLICATION**

For enclosure or 19-in. rack applications, the Blower Fan Package provides the maximum amount of cooling air in the least amount of space by utilizing 115 volt AC, 60/50 hertz, single-phase input power. Engineered for 20,000 hours of continuous operation when properly powered.

### **FEATURES**

- Intake grille is easily removed with two captive thumbnuts
- Washable aluminum filter
- Single phase motor powers the statically balanced blower
- Motor is thermally protected and cooled by incoming forced air
- Direct drive induction motor contains permanently lubricated ball bearings
- Lubricant protects from -20 F to 298 F (-29 C to 148 C)

- Rotating components are suspended on neoprene shock-mounts
  Three-conductor power cord (five feet long)
- The unit is self-supporting with 16 gauge steel flanges notched per EIA RS-310-D.
- An exhaust grille and filter package (catalog number AEXGR275) is required and must be ordered separately

#### **SPECIFICATIONS**

• 16 gauge steel housing

#### **FINISH**

- Blower housing is black enamel.
- Grille is brushed stainless steel.

#### **ACCESSORIES**

Exhaust Grille and Filter Filter Adhesive Temperature Control Switch

## Performance Data Rack-Mountable Fan Package


| CATALOG NUMBERS                |           |
|--------------------------------|-----------|
|                                | ADB275    |
| ELECTRICAL DATA                |           |
| Rated Voltage                  | 115       |
| Frequency                      | 50/60     |
| Free Airflow (CFM)             | 230/275   |
| RPM                            | 2580/3100 |
| Nominal Current Maximum (Amps) | 1.2       |
| Power Consumption (Watts)      | 84        |
| SOUND LEVEL                    |           |
| Sound Pressure (dBA)           | 56        |
| UNIT CONSTRUCTION              |           |
| Weight (lb./kg)                | 15/7      |
| EXHAUST GRILLE CATALOG NUMBERS |           |
| Catalog Number                 | AEXGR275* |
|                                |           |

<sup>\*</sup> Exhaust grille sold separately




# Rack-Mountable Fan Package


Mounting Cutout Dimensions




Blower Cutout



Exhaust Grille Cutout




87541398



### **EXHAUST GRILLES AND REPLACEMENT FILTERS**



Located at air discharge side of an enclosure using Blower Package ADB275. Polished stainless steel grille is 65 percent open and offers low resistance to airflow. Expanded aluminum filter (included with each grille) is easily removed for cleaning from outside the enclosure. Mounting hardware is furnished.



**CUTOUT DIMENSIONS** 

# Performance Data Exhaust Grilles and Replacement Filters for Rack-Mountable Fan Package

| CATALOG NUMBERS           |   |
|---------------------------|---|
|                           | AEXGR275                                    |
| UNIT CONSTRUCTION         |   |
| Dimensions H x W (in./mm) | 5.75/146 x 19.00/483                        |
| Filter Size (in./mm)      | 4.98/126 x 16.56/421                        |
| ACCESSORIES               |   |
| Replacement Filters:      |   |
| Catalog Number            | AFLTR275AL                                  |
| Description               | Aluminum Filter Replacement (5 per package) |