



ALTV248ULCBHI

UL Listed AC Isolated CCTV Power Supply

Rev. DSALTV248ULCBHI_05022014



ALTV248ULCBHI

Overview

ALTV248ULCBHI Isolated CCTV Power Supply provides 24VAC distributed via eight (8) isolated Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 3 amp.

Output:

- Eight (8) Class 2 Rated PTC protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current.
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 153.55 BTU/Hr.
- System AC input VA requirement: 345VA.

Features:

- Illuminated master power disconnect circuit breaker with manual reset.
- Unit maintains camera synchronization.
- Spare fuses provided.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).
- Product weight (approx.): 12.7 lbs. (5.76 kg).
- Shipping weight (approx.): 13.4 lbs. (6.08 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D approximate):
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

