


[On Line Catalog](#)


BURNDY Catalog Number
UPC Number
Description
Status

YSR2CFX4CFXLTKITC
 781810429419
 HYRDC 2F- 4F STD CLR
 Active

Web Use
 BURNDY Product Line

Length (in)
 B Length (in)
 Strip Length

Dimensional

1.79
 0.82
 0.78

General

Product Description

In-line Reducer Splice Kit w/ Clear
 HSS, Reducer: 2 Flex (Barrel A)/4
 Flex (Barrel B), 1.79" Splice
 Length

Conductor(s)

Flex (Class H) Side A - Range 2 AWG
 Flex (Class M) Side B - Range 4 AWG
 Flex (Class K) Side A - Range 2 AWG
 Flex (Class G) Side B - Range 4 AWG
 Flex (Class I) Side A - Range 2 AWG
 Flex (Class H) Side B - Range 4 AWG
 Flex (Class I) Side B - Range 4 AWG
 Flex (Class M) Side A - Range 2 AWG
 Flex (Class G) Side A - Range 2 AWG
 Flex (Class K) Side B - Range 4 AWG

Physical

Type of Plating Tin - Electro Plated
 Plated (Yes or No) Y

Approvals / Certifications

UL Listed N
 CSA Certified N
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Services

47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175