

AX105215-B25 Modular Connectors - FX BRILLIANCE UNIVERSAL BOOT

For more Information
please call

1-800-Belden1



General Description:

FX BRILLIANCE UNIVERSAL JACKETED 3MM BOOT 25/PACK

Image

Image:



Usage (Overall)

Suitable Applications:	Field-termination of fiber optic cables within Patch Panels, Distribution Frames, Workstation Outlets for FTTH (Fiber to the Home), drops for FTTH (Fiber to the home) and MDU (Multiple Dwelling Units).
Related Parts:	FX Brilliance Precision Installation Kit, FX Brilliance Universal Connectors

Physical Characteristics (Connectivity)

Color

Color:	Black
---------------	-------

Weight

Weight:	0.033 lbs.
----------------	------------

Packaging

Packaging:	Twenty-five (25) boots in bag
-------------------	-------------------------------

Mechanical Characteristics (Connectivity)

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
MII Order #39 (China RoHS):	EUP 50
Telecommunications Standards:	TIA 568-C.3
Safety Listing:	ACA

Suitability

Suitability - Indoor:	Yes - Indoor
------------------------------	--------------

Transmission Characteristics (Connectivity)

Notes (Overall)

AX105215-B25 Modular Connectors - FX BRILLIANCE UNIVERSAL BOOT

Notes: Please refer to Installation Guide PX105234 for installation procedures.

Notes (Cont'd.):

For additional information, please contact our Technical Support
(ibdn.ts@belden.com) or your local sales rep.

Product Family**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 03-17-2014

© 2014 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.