Product Data Sheet | Anixter Catalog Page



Security/Alarm/Access Control/Sound Low-voltage Cable Shielded Non-Plenum

Product Description

- PVC
- Bare Copper Conductor
- UL Listed Type CMR, CL3R

Applications

 For use in security systems, intercom systems, sound/audio systems, access control, power-limited controls.




CONDUCTOR: Bare copper

INSULATION: Polyvinyl Chloride (PVC)
JACKET: Polyvinyl Chloride (PVC), Gray

• STANDARDS: NEC: CMR (22-16 AWG), CL3R (14-12 AWG)

• TEMPERATURE: 75°C



	Conductor	No. of			<u>Insulation</u>	Overall Jacket	Nom. O.D.	Approx. Wt.
Part No.	Size AWG	Conductors	Rating	<u>Insulation</u>	Thickness (in.)	Thickness (in.)	<u>(in.)</u>	lb./1,000 ft.
AL-2202C-2-1S-01	22	2	CMR	PVC	0.007	0.015	0.112	12
AL-2202C-1-1S-01	22 (SOL)	2	CMR	PVC	0.007	0.015	0.121	14
AL-2203C-2-1S-01	22	3	CMR	PVC	0.007	0.015	0.118	14
AL-2204C-2-1S-01	22	4	CMR	PVC	0.007	0.015	0.129	19
AL-2204C-1-1S-01	22 (SOL)	4	CMR	PVC	0.007	0.015	0.119	19
AL-2206C-2-1S-01	22	6	CMR	PVC	0.007	0.015	0.170	27
AL-2208C-2-1S-01	22	8	CMR	PVC	0.007	0.015	0.183	32
AL-2210C-2-1S-01	22	10	CMR	PVC	0.007	0.018	0.189	42
AL-2212C-2-1S-01	22	12	CMR	PVC	0.007	0.015	0.110	44
AL-2002C-2-1S-01	20	2	CMR	PVC	0.008	0.015	0.129	17

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

Anixter is a leading global supplier of communications and security products, electrical and electronic wire and cable, fasteners and other small components. We help our customers specify solutions and make informed purchasing decisions around technology, applications and relevant standards. Throughout the world, we provide innovative supply chain management solutions to reduce our customers' total cost of production and implementation.

Product Data Sheet | Anixter Catalog Page



	Conductor	No. of			<u>Insulation</u>	Overall Jacket	Nom. O.D.	Approx. Wt.
Part No.	Size AWG	Conductors	Rating	<u>Insulation</u>	Thickness (in.)	Thickness (in.)	<u>(in.)</u>	lb./1,000 ft.
AL-2003C-2-1S-01	20	3	CMR	PVC	0.008	0.015	0.150	20
AL-2004C-2-1S-01	20	4	CMR	PVC	0.008	0.015	0.110	23
AL-1802C-2-1S-01	18	2	CMR	PVC	0.008	0.015	0.150	25
AL-1803C-2-1S-01	18	3	CMR	PVC	0.008	0.015	0.160	29
AL-1804C-2-1S-01	18	4	CMR	PVC	0.008	0.015	0.177	37
AL-1806C-2-1S-01	18	6	CMR	PVC	0.008	0.015	0.224	55
AL-1808C-2-1S-01	18	8	CMR	PVC	0.008	0.015	0.259	66
AL-1602C-2-1S-01	16	2	CMR	PVC	0.009	0.015	0.174	30
AL-1604C-2-1S-01	16	4	CMR	PVC	0.009	0.015	0.212	58
AL-1402C-2-1S-01	14	2	CL3R	PVC	0.010	0.017	0.229	50
AL-1404C-2-1S-01	14	4	CL3R	PVC	0.010	0.017	0.261	67
AL-1202C-2-1S-01	12	2	CL3R	PVC	0.011	0.017	0.274	69

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com