



6-557315-3 | MP-88U-R-1  
**Modular Plug, 8P/8C, Unshielded, Round, 100 pcs**

## Body Features

Conductor Type	Solid   Stranded
----------------	------------------

## Configuration Features

Number of Positions	8
Keyed	No

## Contact Features

Contact Base Material	Phosphor bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.00 µin   1.27 µm
Number of Contacts Loaded	8

## Dimensions

Cable Jacket Outside Diameter Range	0.20 in   5.1 mm
Conductor Outside Diameter	0.034–0.039 in   0.86–0.99 mm
Conductor Wire Size	26–24 AWG

## Housing Features

Housing Material	Glass filled polycarbonate
------------------	----------------------------

## Industry Standards

UL Flammability Rating	UL 1863
------------------------	---------

## Packaging Features

Packaging Quantity	100
--------------------	-----

## Product Availability

Region	Asia   Australia/New Zealand   EMEA   Latin America   North America
--------	---

## Product Type Features

Cable Type	Round, unshielded
Performance Category	Category 5
Connector Style	Plug
Jack Type	RJ45

6-557315-3 | MP-88UR-1

Latch Style	Standard
Product Type	Connector
Shielded	No

## Termination Features

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
----------------------------------	-------------------------------------