



760200352 | 360CM12-4x6-LS

InstaPATCH® 360 4x6 LazrSPEED® Conversion Module, 6 MPO male ports, iPatch Ready

Construction Materials

| | |
|------------------------|---|
| Fiber Type | LazrSPEED® 550, 50 µm multimode fiber (OM4) |
| Total Fibers, quantity | 48 |

Dimensions

| | |
|--------|---------------------|
| Depth | 109.22 mm 4.30 in |
| Height | 27.94 mm 1.10 in |
| Width | 91.44 mm 3.60 in |

Environmental Specifications

| | |
|-----------------|----|
| Safety Standard | UL |
|-----------------|----|

General Specifications

| | |
|------------------------------|-------------------|
| Interface, front | MPO Male |
| Total Ports, quantity, front | 6 |
| Interface Feature, front | Standard |
| Color, front | Aqua |
| Adapters, quantity, front | 6 |
| Brand | InstaPATCH® 360 |
| Color | Black |
| Data Module Type | Standard |
| Intelligence Type | iPatch® ready |
| Interface | MPO |
| Shuttered | No |
| Interface, rear | MPO Male |
| Adapters, quantity, rear | 4 |
| Interface Feature, rear | Reduced footprint |
| Color, rear | Gray |
| Package Quantity | 1 |

Optical Performance

| | |
|------------------------------------|---------|
| Insertion Loss Change, mating | 0.30 dB |
| Insertion Loss Change, temperature | 0.30 dB |
| Insertion Loss, maximum | 0.50 dB |
| Return Loss, minimum | 20.0 dB |

Regulatory Compliance/Certifications

| Agency | Classification |
|--------|----------------|
|--------|----------------|

760200352 | 360CM12-4x6LS

RoHS 2011/65/EU
ISO 9001:2008

* Footnotes

| | |
|------------------------------------|---|
| Insertion Loss Change, mating | Maximum insertion loss change after 500 matings |
| Insertion Loss Change, temperature | Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F) |